

TRANCE X E+ 1

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY (PEDAL ASSIST)	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERY	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGER	Giant EnergyPak 6A smart charger, 60% in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
SIZES	S, M, L, XL
COLOURS	Gloss Cold Night/Cobalt Blue
FRAME	ALUXX SL-grade Aluminium, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FORK	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
SHOCK	Fox Float X Performance, EVOL Large Volume sleeve, 3-Pos Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STEM	Giant Contact SL 35
SEATPOST	Tranz-X Rad+ 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SADDLE	Giant Romero
PEDALS	Flatpedal
DRIVETRAIN	
SHIFTERS	Shimano Deore XT 1x12
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
BRAKES	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm [F], 203mm [R]
BRAKE LEVERS	Shimano Deore XT, I-spec EV
CASSETTE	Shimano CS-M7100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimised
CRANKSET	Praxis Wave tm 36T Cold Forged 4130 premium steel chain ring 104BCD Praxis e-crank arm set (S:160, M/L:165, XL:170) Q-factor=168mm, Chainline: 55mm, Max Chainring: 38T
BOTTOM BRACKET	n/a

WHEELS	
RIMS	Giant AM30, Tubeless ready, 30mm inner width, 29"
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F], e-bike optimised
TYRES	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LOCK	Torx 25 Battery Lock with built-in Torque limiter

Price: £5,999.00

GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	425	450	475
Seat Tube Angle	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	577 575	610 605	637 635	667 665
Head Tube Length (mm)	95	100	110	120
Head Tube Angle	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	117 122.4	117 122.4	117 122.4	117 122.4
Wheelbase (mm)	1205 1206	1239 1237	1268 1269	1300 1301
Chain Stay Length (mm)	473 473	473 473	473 473	473 473
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Stand Over Height (mm)	783 789	775 784	763 770	775 782
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	40	50	50	60
Crank Length (mm)	160	165	165	170
Wheel Size	29"	29"	29"	29"

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.