

TRANCE X E+ 1

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY (ASISTENCIA AL PEDALEO)	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
MANDO	Giant RideControl Ergo3, grip integrated remote
PANTALLA	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERÍA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONECTIVIDAD	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CUADRO	
TALLAS	S, M, L, XL
COLORES	Cold Night / Cobalt
CUADRO	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
HORQUILLA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
AMORTIGUADOR	Fox Float X Performance, EVOL Large Volume sleeve, 3-Pos Lever, 185x52.5mm Trunnion mount, recommended sag: 30%
COMPONENTES	
MANILLAR	Giant Contact 35 Trail, 35x780mm
PUÑOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCIA	Giant Contact SL 35
TIJA DE SILLÍN	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SILLÍN	Giant Romero E
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore XT
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano Deore XT, 12-speed, Shadow+
FRENOS	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm [F], 203mm [R]
PALANCAS DE FRENOS	Shimano Deore XT, I-spec EV
CASETTE	Shimano CS-M7100-12, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
JGO. PLATOS Y BIELAS	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
CAJA DE PEDALIER	n/a

RUEDAS	
LLANTAS	Giant AM30, Tubeless ready, 30mm inner width, 29"
BUJES	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RADIOS	Sapim E-Lite [R] Race [F], e-bike optimized
CUBIERTAS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESORIOS	
CANDADO/ANTI-ROBO	Torx 25 Battery Lock with built-in Torque limiter

Precio: 6.499,00 €

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud del tubo del sillín (mm)	400		425		450		475	
Ángulo del tubo del sillín	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Longitud del tubo superior (mm) (mm)	577	575	610	605	637	635	667	665
Longitud del tubo de dirección (mm) (mm)	95		100		110		120	
Ángulo del tubo de dirección	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Inclinación de la horquilla (mm)	44		44		44		44	
Trail (mm) (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Distancia entre ejes (mm) (mm)	1205	1206	1239	1237	1268	1269	1300	1301
Longitud de la vaina (mm) (mm)	473	473	473	473	473	473	473	473
Caída del eje de pedalier (mm) (mm)	30	20	30	20	30	20	30	20
Stack (mm) (mm)	606	601	611	605	621	614	630	624
Reach (mm) (mm)	439	447	457	462	482	489	510	517
Altura del suelo al tubo (mm) (mm)	783	789	775	784	763	770	775	782
Ancho del manillar (mm) (mm)	780		780		780		780	
Longitud de la potencia (mm) (mm)	40		50		50		60	
Longitud de las bielas (mm) (mm)	160		165		165		170	
Tamaño de ruedas	29"		29"		29"		29"	

Giant se reserva el derecho a modificar especificaciones, precios o colores sin previo aviso.