

TRANCE X E+ 1

GIANT



ESPECIFICACIONES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATERÍA	EnergyPak Smart 750Wh, EnergyPak Plus range extender compatible
CUADRO	
TALLAS	S, M, L, XL
COLORES	Amber Glow
CUADRO	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derailleur hanger, Giant EnergyPak Plus Range Extender Compatible
TIJERA	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip Damper, Boost 110x15QR, e-optimized
AMORTIGUADOR	Fox Float X Performance, EVOL Large Volume sleeve, 3-Pos Lever, 185x52.5mm Trunnion mount
COMPONENTES	
MANUBRIO	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
POTENCIA	Giant Contact SL 35
POSTE DE ASIENTO	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
ASIENTO	Giant Romero Trail
PEDALES	Flat pedal
TRANSMISIÓN	
MANETAS DE CAMBIO	Shimano Deore XT
DESVIADOR	MRP HD2 co-moulded chain guide
CAMBIO TRASERO	Shimano Deore XT, 12-speed, Shadow+
FRENOS	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm
PALANCAS DE FRENOS	Shimano Deore XT BL-M8100, I-spec EV
CASSETTE	Shimano CS-M7100-12, 10-51T, 12-speed
CADENA	KMC e.12 Turbo, EcoProteg, e-bike optimized
MULTIPLICACIÓN	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
EJE DE CENTRO	-

RUEDAS	
RUEDAS	Giant AM 29", Tubeless ready, 30mm inner width
MAZAS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYOS	Sapim E-Lite [R] Race [F]
NEUMÁTICOS	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)

Precio: \$169,900.00

GEOMETRÍA

CUADRO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longitud de la Base del Poste de Asiento (mm)	400		425		450		475	
Ángulo de la Base del Poste de Asiento	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°	76.0°	76.7°
Longitud del Tubo Superior (mm)	577	575	610	605	637	635	667	665
Longitud del Telescopio (mm)	95		100		110		120	
Ángulo del Telescopio	65.7°	66.5°	65.8°	66.5°	65.8°	66.5°	65.8°	66.5°
Rake (mm)	44		44		44		44	
Trail (mm)	117	122.4	117	122.4	117	122.4	117	122.4
Distancia entre Ejes (mm)	1205	1206	1239	1237	1268	1269	1300	1301
Longitud de Vaina Inferior (mm)	473	473	473	473	473	473	473	473
Caída del Eje de Centro (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Altura del Tubo Superior al Suelo (mm)	783	789	775	784	763	770	775	782
Ancho del Manubrio (mm)	780		780		780		780	
Longitud de la Potencia (mm)	40		40		50		50	
Longitud de la Biela (mm)	160		165		165		170	
Tamaño de las Ruedas	29"		29"		29"		29"	

Todas las especificaciones están sujetas a cambios sin previo aviso.