

# TRANCE X E+ 1

GIANT



## TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
OHJAUSYKSIKKÖ	Giant RideControl Ergo3, grip integrated remote
NÄYTTÖ	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
LATURI	Giant EnergyPak 6A smart charger, 60% in 2:15h
YHTEYDET MUIHIN LAITTEISIIN	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Cold Night / Cobalt
RUNKO	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
HAARUKKA	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
ISKUNVAIMENNIN	Fox Float X Performance, EVOL Large Volume sleeve, 3-Pos Lever, 185x52.5mm Trunnion mount, recommended sag: 30%
KOMPONENTIT	
OHJAUSTANKO	Giant Contact 35 Trail, 35x780mm
GRIPIT	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
OHJAINKANNATIN	Giant Contact SL 35
SATULATOLPPA	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SATULA	Giant Romero E
POLKIMET	Flat pedal
VOIMANSIIRTO	
VAIHDEVIPU	Shimano Deore XT
ETUVAIHTAJA	MRP HD2 co-moulded chain guide
TAKAVAIHTAJA	Shimano Deore XT, 12-speed, Shadow+
JARRUT	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm [F], 203mm [R]
JARRUKAHVAT	Shimano Deore XT, I-spec EV
RATASPAKKA	Shimano CS-M7100-12, 10-51T, 12-speed
KETJUT	KMC e.12 Turbo, EcoProtege, e-bike optimized
KAMPISARJA	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
KESKIÖ	n/a

RENKAAT	
VANTEET	Giant AM30, Tubeless ready, 30mm inner width, 29"
NAVAT	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
PINNAT	Sapim E-Lite [R] Race [F], e-bike optimized
RENKAAT	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
LISÄTIEDOT	Tubeless kit (liquid, valves, levers, manual, tool)
TARVIKKEET	
LUKKO	Torx 25 Battery Lock with built-in Torque limiter

Suositusuhinta: 7 159,00 €

## GEOMETRIA

RUNKO	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Satulaputken pituus (mm)	400		425		450	
Satulaputken kulma	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Vaakaputken pituus (mm)	577	575	610	605	637	635
Emäputken pituus (mm)	95		100		110	
Emäputken kulma	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°
Haarukan offset (mm)	44		44		44	
Trail-mitta (mm)	117	122,4	117	122,4	117	122,4
Akseliväli (mm)	1205	1206	1239	1237	1268	1269
Takahaarukan alaputken pituus (mm)	473	473	473	473	473	473
Keskilön pudotus (mm)	30	20	30	20	30	20
Stack-mitta (mm)	606	601	611	605	621	614
Reach-mitta (mm)	439	447	457	462	482	489
Standover-mitta (mm)	783	789	775	784	763	770
Ohjaustangon leveys (mm)	780		780		780	
Ohjainkannattimen pituus (mm)	40		50		50	
Kammen pituus (mm)	160		165		165	
Rengaskoko	29"		29"		29"	

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.