

TRANCE X E+ 1

GIANT



TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro 2, 85Nm, powered by Yamaha
COMMANDE	Giant RideControl Ergo3, grip integrated remote
ECRAN	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIE	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CHARGEUR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITÉ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
TAILLES	S, M, L, XL
COLORIS	Cold Night / Cobalt
CADRE	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FOURCHE	Fox 36 Float Performance E-Tuned, 29er, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Kabolt-X 110
AMORTISSEUR	Fox Float X Performance, EVOL Large Volume sleeve, 3-Pos Lever, 185x52.5mm Trunnion mount, recommended sag: 30%
COMPOSANTS	
CINTRE	Giant Contact 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SELLE	Giant Romero E
PÉDALES	Flat pedal
DÉRAILLEUR	
MANETTES	Shimano Deore XT
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore XT, 12-speed, Shadow+
FREINS	Shimano Deore XT, BR-M8120, 4-piston, hydraulic disc, 220mm [F], 203mm [R]
LEVIERS DE FREIN	Shimano Deore XT, I-spec EV
CASSETTE	Shimano CS-M7100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProtege, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOITIER DE PÉDALIER	n/a

ROUES	
JANTES	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOYEURS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
ANTI-VOL	Torx 25 Battery Lock with built-in Torque limiter
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 6 100,00 €

GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Longueur du tube supérieur (mm)	577	575	610	605	637	635	667	665
Longueur du tube de direction (mm)	95	100	110	120				
Angle du tube de direction	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Empattement (mm)	1205	1206	1239	1237	1268	1269	1300	1301
Longueur des bases (mm)	473	473	473	473	473	473	473	473
Drop du boîtier de pédalier (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Hauteur en statique (mm)	783	789	775	784	763	770	775	782
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	50	50	60				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des roues	29"	29"	29"	29"				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.