



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERY	EnergyPak Smart 625Wh, EnergyPak Plus range extender compatible
FRAME	
SIZES	S, M, L, XL
COLORS	Sapphire
FRAME	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derailleur hanger, Giant EnergyPak Plus Range Extender Compatible
FORK	Fox 36 Float Rhythm, 150mm travel, 44mm offset, EVOL, Grip Damper, Sweep adjust, Boost 110x15QR, e-optimized
SHOCK	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
COMPONENTS	
HANDLEBAR	Giant Contact 35 Trail, 35x780mm
GRIPS	Giant Tactal Pro-E, single lock-on
STEM	Giant Contact SL 35
SEATPOST	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
SADDLE	Giant Romero Trail
PEDALS	Flat pedal
DRIVETRAIN	
SHIFTERS	Shimano SLX
FRONT DERAILLEUR	MRP HD2 co-moulded chain guide
REAR DERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
BRAKES	Shimano Deore BR-M6120, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Shimano Deore BL-M6100, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAIN	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

WHEELS	
RIMS	Giant AM 29", Tubeless ready, 30mm inner width
HUBS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPOKES	Sapim E-Lite [R] Race [F]
TIRES	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRY

FRAME	S	XL
	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	475
Seat Tube Angle	76.0° 76.7°	76.0° 76.7°
Top Tube Length (mm)	577 575	667 665
Head Tube Length (mm)	95	120
Head Tube Angle	65.7° 66.5°	65.8° 66.5°
Fork Rake (mm)	44	44
Trail (mm)	117 122.4	117 122.4
Wheelbase (mm)	1205 1206	1300 1301
Chain Stay Length (mm)	473 473	473 473
Bottom Bracket Drop (mm)	30 20	30 20
Stack (mm)	606 601	630 624
Reach (mm)	439 447	510 517
Stand Over Height (mm)	783 789	775 782
Handlebar Width (mm)	780	780
Stem Length (mm)	40	50
Crank Length (mm)	160	170
Wheel Size	29"	29"

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.