

# TRANCE X E+ 2

GIANT



## TECHNIQUES

TECHNOLOGIE HYBRID	
MOTEUR	SyncDrive Pro <sup>2</sup> , 85Nm, powered by Yamaha
COMMANDE	RideControl Ergo 3, grip integrated
ECRAN	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
BATTERIE	EnergyPak Smart 625Wh, EnergyPak Plus range extender compatible
CADRE	
TAILLES	S, M, L, XL
COLORIS	Sapphire
CADRE	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derailleur hanger, Giant EnergyPak Plus Range Extender Compatible
FOURCHE	Fox 36 Float Rhythm E-Bike, 29er, 150mm travel, 44mm offset, Grip damper Sweep adjust, Boost 110x15QR
AMORTISSEUR	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
COMPOSANTS	
CINTRE	Giant Contact 35 Trail, 35x780mm
POIGNÉES	Giant Tactal Pro-E, single lock-on
POTENCE	Giant Contact SL 35
TIGE DE SELLE	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
SELLE	Giant Romero Trail
PÉDALES	Flat pedal
DÉRAILLEUR	
MANETTES	Shimano SLX
DÉRAILLEUR AVANT	MRP HD2 co-moulded chain guide
DÉRAILLEUR ARRIÈRE	Shimano Deore XT, 12-speed, Shadow+
FREINS	Tektro HDM545 4-piston disc brake
LEVIER DE FREIN	Tektro HDM545
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CHAÎNE	KMC e.12 Turbo, EcoProtege, e-bike optimized
PÉDALIER	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOITIER DE PÉDALIER	-

ROUES	
JANTES	Giant AM 29", Tubeless ready, 30mm inner width
MOYEURS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAYONS	Sapim E-Lite [R] Race [F]
PNEUS	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
ECLAIRAGE	Compatible en option : éclairage Giant Recon E+ et Kit d'éclairage avant et arrière à piles
LIMITES	
POIDS TOTAL MAX AUTORISÉ	156 kg (vélo, cycliste et bagages)

Prix Public Conseillé: 5 400,00 €

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	475				
Angle de tube de selle	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°				
Longueur du tube supérieur (mm)	577   575	610   605	637   635	667   665				
Longueur du tube de direction (mm)	95	100	110	120				
Angle du tube de direction	65,7°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°				
Déport de fourche (mm)	44	44	44	44				
Trail (mm)	117   122,4	117   122,4	117   122,4	117   122,4				
Empattement (mm)	1205   1206	1239   1237	1268   1269	1300   1301				
Longueur des bases (mm)	473   473	473   473	473   473	473   473				
Drop du boîtier de pédalier (mm)	30   20	30   20	30   20	30   20				
Stack (mm)	606   601	611   605	621   614	630   624				
Reach (mm)	439   447	457   462	482   489	510   517				
Hauteur en statique (mm)	783   789	775   784	763   770	775   782				
Largeur de cintre (mm)	780	780	780	780				
Longueur de potence (mm)	40	40	50	50				
Longueur des manivelles (mm)	160	165	165	170				
Diamètre des roues	29"	29"	29"	29"				

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.