

# TRANCE X E+ 2

**GIANT**



## TECHNIQUES

TECHNOLOGIE HYBRID	
<b>MOTEUR</b>	SyncDrive Pro 2, 85Nm, powered by Yamaha
<b>COMMANDE</b>	Giant RideControl Ergo3, grip integrated remote
<b>ECRAN</b>	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
<b>BATTERIE</b>	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
<b>CHARGEUR</b>	Giant EnergyPak 6A smart charger, 60% in 2:15h
<b>CONNECTIVITÉ</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
<b>TAILLES</b>	S, M, L, XL
<b>COLORIS</b>	Messier / Black
<b>CADRE</b>	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
<b>FOURCHE</b>	Fox 36 Float Rhythm E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Sweep adjust, Boost 110x15QR
<b>AMORTISSEUR</b>	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
<b>CINTRE</b>	Giant Contact 35 Trail, 35x780mm
<b>POIGNÉES</b>	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
<b>POTENCE</b>	Giant Contact SL 35
<b>TIGE DE SELLE</b>	OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170 -140MM / 172D-CONTAC-0050 total length 530 T200-170MM
<b>SELLE</b>	Giant Romero E
<b>PÉDALES</b>	Flat pedal
DÉRAILLEUR	
<b>MANETTES</b>	Shimano SLX
<b>DÉRAILLEUR AVANT</b>	MRP HD2 co-moulded chain guide
<b>DÉRAILLEUR ARRIÈRE</b>	Shimano SLX, 12-speed, Shadow+
<b>FREINS</b>	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
<b>LEVIERS DE FREIN</b>	Shimano Deore, I-spec EV
<b>CASSETTE</b>	Shimano CS-M6100-12, 10-51T, 12-speed
<b>CHAÎNE</b>	KMC e.12 Turbo, EcoProteq, e-bike optimized
<b>PÉDALIER</b>	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
<b>BOITIER DE PÉDALIER</b>	n/a

ROUES	
<b>JANTES</b>	Giant AM30, Tubeless ready, 30mm inner width, 29"
<b>MOYEURS</b>	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
<b>RAYONS</b>	Sapim E-Lite [R] Race [F], e-bike optimized
<b>PNEUS</b>	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
<b>ECLAIRAGE</b>	Kit d'éclairage avant et arrière à piles
<b>ANTI-VOL</b>	Torx 25 Battery Lock with built-in Torque limiter
LIMITES	
<b>POIDS TOTAL MAX AUTORISÉ</b>	156 kg (vélo, cycliste et bagages)

**Prix Public Conseillé: 5 300,00 €**

## GÉOMÉTRIE

CADRE	S	M	L	XL
Longueur de tube de selle (mm)	LOW   HIGH 400	LOW   HIGH 425	LOW   HIGH 450	LOW   HIGH 475
Angle de tube de selle	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°	76,0°   76,7°
Longueur du tube supérieur (mm)	577   575	610   605	637   635	667   665
Longueur du tube de direction (mm)	95	100	110	120
Angle du tube de direction	65,7°   66,5°	65,8°   66,5°	65,8°   66,5°	65,8°   66,5°
Déport de fourche (mm)	44	44	44	44
Trail (mm)	117   122,4	117   122,4	117   122,4	117   122,4
Empattement (mm)	1205   1206	1239   1237	1268   1269	1300   1301
Longueur des bases (mm)	473   473	473   473	473   473	473   473
Drop du boîtier de pédalier (mm)	30   20	30   20	30   20	30   20
Stack (mm)	606   601	611   605	621   614	630   624
Reach (mm)	439   447	457   462	482   489	510   517
Hauteur en statique (mm)	783   789	775   784	763   770	775   782
Largeur de cintre (mm)	780	780	780	780
Longueur de potence (mm)	40	50	50	60
Longueur des manivelles (mm)	160	165	165	170
Diamètre des roues	29"	29"	29"	29"

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.