

TRANCE X E+ 2

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
BEDIENINGSUNIT	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED displayANT+ Wireless display compatible
ACCU	EnergyPak Smart 625Wh, EnergyPak Plus range extender compatible
FRAME	
MATEN	S, M, L, XL
KLEUREN	Sapphire
FRAME	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derailleur hanger, Giant EnergyPak Plus Range Extender Compatible
VOORVORK	Fox 36 Float Rhythm, 150mm travel, 44mm offset, EVOL, Grip Damper, Sweep adjust, Boost 110x15QR, e-optimized
DEMPER	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
ONDERDELEN	
STUUR	Giant Contact 35 Trail, 35x780mm
HANDVATTEN	Giant Tactal Pro-E, single lock-on
STUURPEN	Giant Contact SL 35
ZADEL	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
ZADEL	Giant Romero Trail
PEDALEN	Flat pedal
AFMONTAGE	
SHIFTERS	Shimano SLX
VOORDERAILLEUR	MRP HD2 co-moulded chain guide
ACHTERDERAILLEUR	Shimano Deore XT, 12-speed, Shadow+
REMMEN	Shimano Deore BR-M6120, 4-piston, hydraulic disc, 203mm
REMHENDELS	Shimano Deore BL-M6100, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
AANDRIJVING	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	-

WIELSET	
VELGEN	Giant AM 29", Tubeless ready, 30mm inner width
NAVEN	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPAKEN	Sapim E-Lite [R] Race [F]
BANDEN	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
VERLICHTING	Optional:- Giant Recon series e-bike lights available and direct connectable

Adviesprijs: € 5.699,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	400	425	450	475				
Zitbuis Hoek	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°		
Frame Lengte (horizontaal) (mm)	577 575	610 605	637 635	667 665				
Balhoofdbuis Lengte (mm)	95	100	110	120				
Balhoofdbuis Hoek	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°		
Vork Sprong (mm)	44	44	44	44				
Naloop (mm)	117 122,4	117 122,4	117 122,4	117 122,4	117 122,4	117 122,4		
Wielbasis (mm)	1205 1206	1239 1237	1268 1269	1300 1301				
Liggende achtervork lengte (mm)	473 473	473 473	473 473	473 473				
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20				
Stack (mm)	606 601	611 605	621 614	630 624				
Reach (mm)	439 447	457 462	482 489	510 517				
Stand Over Height (mm)	783 789	775 784	763 770	775 782				
Stuur breedte (mm)	780	780	780	780				
Stuurpen Lengte (mm)	40	40	50	50				
Cranklengte (mm)	160	165	165	170				
Wielmaat	29"	29"	29"	29"				

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.