

TRANCE X E+ 2



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
ACCU	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
LADER	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
FRAME	
MATEN	S, M, L, XL
KLEUREN	Messier / Black
FRAME	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
VOORVORK	Fox 36 Float Rhythm E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Sweep adjust, Boost 110x15QR
DEMPER	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
ONDERDELEN	
STUUR	Giant Contact 35 Trail, 35x780mm
HANDVATTEN	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
STUURPEN	Giant Contact SL 35
ZADELPEN	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
ZADEL	Giant Romero E
PEDALEN	Flat pedal
AFMONTAGE	
SHIFTERS	Shimano SLX
VOORDERAILLEUR	MRP HD2 co-moulded chain guide
ACHTERDERAILLEUR	Shimano SLX, 12-speed, Shadow+
REMMEN	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
REMHENDELS	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
AANDRIJVING	KMC e.12 Turbo, EcoProteq, e-bike optimized
CRANKSET	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant AM30, Tubeless ready, 30mm inner width, 29"
NAVEN	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPAKEN	Sapim E-Lite [R] Race [F], e-bike optimized
BANDEN	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRA'S	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
SLOT	Torx 25 Battery Lock with built-in Torque limiter

Adviesprijs: € 6.099,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Zitbuis lengte (mm)	400	425	450	475
Zitbuis hoek	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Frame Lengte (horizontaal) (mm)	577 575	610 605	637 635	667 665
Balhoofdbuis Lengte (mm)	95	100	110	120
Balhoofdbuis Hoek	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Wielbasis (mm)	1205 1206	1239 1237	1268 1269	1300 1301
Liggende achtervork lengte (mm)	473 473	473 473	473 473	473 473
Bottom Bracket Drop (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Stand Over Height (mm)	783 789	775 784	763 770	775 782
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	40	50	50	60
Cranklengte (mm)	160	165	165	170
Wielmaat	29"	29"	29"	29"

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.