

TRANCE X E+ 2

GIANT



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
ECRÃ	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATERIA	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARREGADOR	Giant EnergyPak 6A smart charger, 60% in 2:15h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
QUADRO	
TAMANHOS	S, M, L, XL
CORES	Messier / Black
QUADRO	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FORQUILHA	Fox 36 Float Rhythm E-Tuned, 29er, 150mm travel, 44mm offset, Grip Damper, Sweep adjust, Boost 110x15QR
AMORTECEDORES	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTES	
GUIADOR	Giant Contact 35 Trail, 35x780mm
PUNHOS	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
AVANÇO	Giant Contact SL 35
ESPIGÃO DE SELIM	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SELIM	Giant Romero E
PEDAIS	Flat pedal
TRANSMISSÃO	
MANETES	Shimano SLX
DESVIADOR DIANTEIRO	MRP HD2 co-moulded chain guide
DESVIADOR TRASEIRO	Shimano SLX, 12-speed, Shadow+
TRAVÕES	Shimano Deore, BR-M6120, 4-piston, hydraulic disc, 203mm
MANÍPULOS DOS TRAVÕES	Shimano Deore, I-spec EV
CASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
CORRENTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
CONJUNTO PEDALEIRO	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
MOVIMENTO CENTRAL	n/a

RODAS	
AROS	Giant AM30, Tubeless ready, 30mm inner width, 29"
CUBOS	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAIOS	Sapim E-Lite [R] Race [F], e-bike optimized
PNEUS	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACESSÓRIOS	
CADEADO	Torx 25 Battery Lock with built-in Torque limiter

Preço: 4 999,00 €

GEOMETRIA

QUADRO	S		M		L		XL	
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH	
Comprimento do tubo do assento (mm)	400	425	450	475				
Ângulo do tubo do assento	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°				
Comprimento do tubo superior (mm)	577 575	610 605	637 635	667 665				
Comprimento do tubo principal (mm)	95	100	110	120				
Ângulo do tubo principal	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°				
Garfo ancinho (mm)	44	44	44	44				
Trilha (mm)	117 122,4	117 122,4	117 122,4	117 122,4				
distância entre eixos (mm)	1205 1206	1239 1237	1268 1269	1300 1301				
Comprimento Chain Stay (mm)	473 473	473 473	473 473	473 473				
Suporte inferior (mm)	30 20	30 20	30 20	30 20				
Pilha (mm)	606 601	611 605	621 614	630 624				
Alcançar (mm)	439 447	457 462	482 489	510 517				
Altura do standover (mm)	783 789	775 784	763 770	775 782				
Largura do guidão (mm)	780	780	780	780				
Comprimento da haste (mm)	40	50	50	60				
Comprimento da Manivela (mm)	160	165	165	170				
Tamanho da roda	29"	29"	29"	29"				

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.