

# TRANCE X E+ 3

**GIANT**



## TECHNIQUES

TECHNOLOGIE HYBRID	
<b>MOTEUR</b>	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
<b>COMMANDE</b>	Giant RideControl Ergo3, grip integrated remote
<b>ECRAN</b>	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
<b>BATTERIE</b>	Giant EnergyPak 750Wh, Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
<b>CHARGEUR</b>	Giant EnergyPak 6A smart charger, 60% in 2:10h
<b>CONNECTIVITÉ</b>	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRE	
<b>TAILLES</b>	S, M, L, XL
<b>COLORIS</b>	Cordovan/Copper Coin
<b>CADRE</b>	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
<b>FOURCHE</b>	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControltm rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
<b>AMORTISSEUR</b>	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPOSANTS	
<b>CINTRE</b>	Giant Contact 35 Trail, 35x780mm
<b>POIGNÉES</b>	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
<b>POTENCE</b>	Giant Contact SL 35
<b>TIGE DE SELLE</b>	OBC Giant Contact Switch AT Travel adjustable 172D-CONTAC-0053 total length 315 T100-70MM / 172D-CONTAC-0052 total length 395 T140-110MM / 172D-CONTAC-0051 total length 470 T170 -140MM / 172D-CONTAC-0050 total length 530 T200-170MM
<b>SELLE</b>	Giant Romero E
<b>PÉDALES</b>	Flat pedals
DÉRAILLEUR	
<b>MANETTES</b>	Shimano Deore
<b>DÉRAILLEUR AVANT</b>	MRP HD2 co-moulded chain guide
<b>DÉRAILLEUR ARRIÈRE</b>	Shimano Deore, 12-speed
<b>FREINS</b>	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
<b>LEVIERS DE FREIN</b>	Shimano Deore, I-spec EV
<b>CASSETTE</b>	Shimano CS-M6100-12, 10-51T, 12-speed
<b>CHAÎNE</b>	KMC e.12 Turbo, EcoProteq, e-bike optimized
<b>PÉDALIER</b>	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
<b>BOITIER DE PÉDALIER</b>	n/a

ROUES	
<b>JANTES</b>	Giant AM30, Tubeless ready, 30mm inner width, 29"
<b>MOYEURS</b>	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
<b>RAYONS</b>	Sapim E-Lite [R] Race [F], e-bike optimized
<b>PNEUS</b>	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
<b>EXTRAS</b>	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSOIRES	
<b>ECLAIRAGE</b>	Kit d'éclairage avant et arrière à piles
<b>ANTI-VOL</b>	Torx 25 Battery Lock with built-in Torque limiter
LIMITES	
<b>POIDS TOTAL MAX AUTORISÉ</b>	156 kg (vélo, cycliste et bagages)

**Prix Public Conseillé: 4 800,00 €**

## GÉOMÉTRIE

CADRE	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Longueur de tube de selle (mm)	400	425	450	450	475	475		
Angle de tube de selle	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°	76,0°	76,7°
Longueur du tube supérieur (mm)	577	575	610	605	637	635	667	665
Longueur du tube de direction (mm)	95	100	110	110	120	120		
Angle du tube de direction	65,7°	66,5°	65,8°	66,5°	65,8°	66,5°	65,8°	66,5°
Déport de fourche (mm)	44	44	44	44	44	44		
Trail (mm)	117	122,4	117	122,4	117	122,4	117	122,4
Empattement (mm)	1205	1206	1239	1237	1268	1269	1300	1301
Longueur des bases (mm)	473	473	473	473	473	473	473	473
Drop du boîtier de pédalier (mm)	30	20	30	20	30	20	30	20
Stack (mm)	606	601	611	605	621	614	630	624
Reach (mm)	439	447	457	462	482	489	510	517
Hauteur en statique (mm)	783	789	775	784	763	770	775	782
Largeur de cintre (mm)	780	780	780	780	780	780		
Longueur de potence (mm)	40	50	50	50	60	60		
Longueur des manivelles (mm)	160	165	165	165	170	170		
Diamètre des roues	29"	29"	29"	29"	29"	29"		

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016). GIANT France se réserve le droit de modifier les spécifications sans préavis.