



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	SyncDrive Pro, 85Nm, powered by Yamaha
COMANDO	RideControl Ergo 3, grip integrated
DISPLAY	RideControl GO, frame integrated LED display ANT+ Wireless display compatible
BATTERIA	EnergyPak Smart 625Wh, EnergyPak Plus range extender compatible
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Black Diamond
TELAIO	ALUXX SL-Grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH derailleur hanger, Giant EnergyPak Plus Range Extender Compatible
FORCELLA	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
AMMORTIZZATORE	Rock Shox Deluxe R, 185x52.5mm Trunion mount, custom tuned
COMPONENTISTICA	
MANUBRIO	Giant Contact 35 Trail, 35x780mm
MANOPOLE	Giant Tactal Pro-E, single lock-on
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISSELLA	Giant Contact Switch, dropper, 30,9mm (S:125, M: 150, L/XL:170)
SELLA	Giant Romero Trail
PEDALI	Flat pedal
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore
DERAGLIATORE ANTERIORE	MRP HD2 co-moulded chain guide
DERAGLIATORE POSTERIORE	Shimano Deore 12-speed
FRENI	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Shimano Deore BL-M4100, I-spec EV
PACCO PIGNONI	Shimano CS-M6100-12, 10-51T, 12-speed
CATENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GUARNITURA	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160, M/L: 165, XL:170)
MOVIMENTO CENTRALE	-

RUOTE	
CERCHI	Giant AM 29", Tubeless ready, 30mm inner width
MOZZI	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAGGI	Sapim E-Lite [R] Race [F]
COPERTONI	Maxxis Assegai 29x2.6" foldable, Tubeless, EXO [F] Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+ [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
ILLUMINAZIONE	Optional:- Giant Recon series e-bike lights available and direct connectable

Prezzo: 4.949,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Lunghezza Tubo Sella (mm)	400	425	450	475
Angolo Tubo Sella	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Lunghezza Tubo Orizzontale (mm)	577 575	610 605	637 635	667 665
Lunghezza Tubo Sterzo (mm)	95	100	110	120
Angolo Sterzo	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Interasse (mm)	1205 1206	1239 1237	1268 1269	1300 1301
Lunghezza Carro Posteriore (mm)	473 473	473 473	473 473	473 473
Drop Movimento Centrale (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Altezza stand over (mm)	783 789	775 784	763 770	775 782
Larghezza Manubrio c/c (mm)	780	780	780	780
Lunghezza Attacco Manubrio (mm)	40	40	50	50
Lunghezza Pedivella (mm)	160	165	165	170
Dimensione Ruote	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.