

TRANCE X E+ 3



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTORE	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
COMANDO	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
BATTERIA	Giant EnergyPak 750Wh, Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production Giant EnergyPak Plus 250 range extender compatible
CARICATORE	Giant EnergyPak 6A smart charger, 60% in 2:10h
CONNETTIVITÀ	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Cordovan/Copper Coin
TELAIO	ALUXX SL-grade Aluminum, Advanced Forged Composite linkage, 140mm Maestro Suspension System, 'Boost' 148x12 UDH rear axle, Giant EnergyPak Plus Range Extender Compatible
FORCELLA	RockShox 35 Gold RL DebonAir, 150mm travel, 44mm offset, MotionControl™ rebound and lockout control, 15x110 Boost, Maxle Stealth, e-MTB optimized
AMMORTIZZATORE	Rock Shox Deluxe Select R, DebonAir, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
COMPONENTISTICA	
MANUBRIO	Giant Contact 35 Trail, 35x780mm
MANOPOLE	Giant Tactal Pro-E, tapered design, 135mm Ø28–30mm (S/M) 142mm Ø29–32mm (L/XL)
ATTACCO MANUBRIO	Giant Contact SL 35
REGGISSELLA	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SELLA	Giant Romero E
PEDALI	Flat pedals
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano Deore
DERAGLIATORE ANTERIORE	MRP HD2 co-moulded chain guide
DERAGLIATORE POSTERIORE	Shimano Deore, 12-speed
FRENI	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
COMANDI FRENO	Shimano Deore, I-spec EV
PACCO PIGNONI	Shimano CS-M6100-12, 10-51T, 12-speed
CATENA	KMC e.12 Turbo, EcoProteq, e-bike optimized
GUARNITURA	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
MOVIMENTO CENTRALE	n/a

RUOTE	
CERCHI	Giant AM30, Tubeless ready, 30mm inner width, 29"
MOZZI	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
RAGGI	Sapim E-Lite [R] Race [F], e-bike optimized
COPERTONI	Maxxis Minion DHF 29x2.6" foldable, Tubeless, EXO+, 3C MaxxTerra [F]Maxxis Dissector 29x2.6" Foldable, Tubeless, EXO+, 3C MaxxTerra [R]
EXTRA	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORI	
LUCCHETTO	Torx 25 Battery Lock with built-in Torque limiter

Prezzo: 5.199,00 €

GEOMETRIA

TELAIO	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Lunghezza Tubo Sella (mm)	400	425	450	475
Angolo Tubo Sella	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°	76,0° 76,7°
Lunghezza Tubo Orizzontale (mm)	577 575	610 605	637 635	667 665
Lunghezza Tubo Sterzo (mm)	95	100	110	120
Angolo Sterzo	65,7° 66,5°	65,8° 66,5°	65,8° 66,5°	65,8° 66,5°
Rake Forcella (mm)	44	44	44	44
Avancorsa (mm)	117 122,4	117 122,4	117 122,4	117 122,4
Interasse (mm)	1205 1206	1239 1237	1268 1269	1300 1301
Lunghezza Carro Posteriore (mm)	473 473	473 473	473 473	473 473
Drop Movimento Centrale (mm)	30 20	30 20	30 20	30 20
Stack (mm)	606 601	611 605	621 614	630 624
Reach (mm)	439 447	457 462	482 489	510 517
Altezza stand over (mm)	783 789	775 784	763 770	775 782
Larghezza Manubrio c/c (mm)	780	780	780	780
Lunghezza Attacco Manubrio (mm)	40	50	50	60
Lunghezza Pedivella (mm)	160	165	165	170
Dimensione Ruote	29"	29"	29"	29"

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.