

TRANCE X SX



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Golden Haze
RAHMEN	ALUXX SL-Grade Aluminum front and rear triangles, 145mm Maestro suspension, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
GABEL	Fox 36 Float Rhythm, 160mm, GRIP damper, 15x110 Kabolt X, 44mm offset
DÄMPFER	Marzocchi Bomber Air, two-position compression sweep, 185/55, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single Lock-On, 132x35mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATTELSTÜTZE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SATTEL	Giant Romero SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Deore, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano Deore, Shadow +
BREMSEN	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSHEBEL	Shimano Deore BL-MT401
KASSETTE	Shimano Deore M6100, 10x51
KETTE	KMC X-12
KURBEL	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	Praxis, press fit

LAUFRÄDER	
FELGEN	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
NABE	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
SPEICHEN	Sapim, 28, J-bend
REIFEN	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 27.5x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Sitzrohrwinkel	75.5°	75.9°	76.3°	75.6°	75.9°	76.3°	75.6°	76.0°	76.3°	75.7°	76.0°	
Oberrohrlänge (mm)	574	573	572	605	604	603	627	626	626	660	659	658
Steuerrohr-Länge (mm)	100			105			115			125		
Steuerrohr-Winkel	63.1°	63.5°	63.9°	63.2°	63.5°	63.9°	63.2°	63.6°	63.9°	63.3°	63.6°	
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	143.9	141.1	138.1	143.6	140.8	138	143.3	140.6	137.8	143	140.4	137.6
Radstand (mm)	1194	1193	1193	1226	1225	1225	1250	1250	1249	1285	1284	1284
Kettenstreben-Länge (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Tretlager-Höhe (mm)	30	25	21	31	26	21	30	26	21	31	26	21
Stack (mm)	626	623	621	631	628	625	640	638	635	650	647	644
Reach (mm)	413	417	421	443	447	451	463	467	471	494	497	500
Überstandshöhe (mm)	725	729	734	739	743	748	762	760	765	773	778	783
Vorbaulänge (mm)	40			40			50			50		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.