



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	S, M, L, XL
COLORIS	Golden Haze
CADRE	ALUXX SL-Grade Aluminum front and rear triangles, 145mm Maestro suspension, 12x148mm thru-axle, 27.5-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
FOURCHE	Fox 36 Float Rhythm, 160mm, GRIP damper, 15x110 Kabolt X, 44mm offset
AMORTISSEUR	Marzocchi Bomber Air, two-position compression sweep, 185/55, custom tuned for Giant
COMPOSANTS	
CINTRE	Giant Contact TR35, alloy, 780x35mm, 20mm rise
POIGNÉES	Giant Tactal Pro Single Lock-On, 132x35mm
POTENCE	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
TIGE DE SELLE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SELLE	Giant Romero SL
PÉDALES	N/A
DÉRAILLEUR	
MANETTES DÉRAILLEUR	Shimano Deore, 1x12
DÉRAILLEUR AVANT	N/A
DÉRAILLEUR ARRIÈRE	Shimano Deore, Shadow +
FREINS	Shimano BR-MT420, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
LEVIERS DE FREIN	Shimano Deore BL-MT401
CASSETTE	Shimano Deore M6100, 10x51
CHAÎNE	KMC X-12
PÉDALIER	Praxis Cadet HD M24, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
PÉDALIER	Praxis, press fit

ROUES	
JANTES	Giant TRA 2 wheelset, 6061 alloy, hookless, 30mm inner width, 40mm outer width, 21mm height, Wide Guard Technology
MOYEUX	[F] Giant MTB alloy, six-bolt [R] Giant MTB alloy, 72t POE (Points of Engagement), six-bolt, MicroSpline driver body
RAYONS	Sapim, 28, J-bend
PNEUS	[F] Maxxis Minion DHF, 29x2.5 WT, 60 tpi, EXO, TR [R] Maxxis Dissector 27.5x2.4 WT, 60 tpi, EXO TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GÉOMÉTRIE

CADRE	S			M			L			XL
	LOW MID HIGH			LOW MID HIGH			LOW MID HIGH			LOW MID HIGH
Longueur de tube de selle (mm)	400			425			450			475
Seat Post Insertion Depth (mm)	280			305			330			355
Angle de tube de selle	75,5° 75,9° 76,3°			75,6° 75,9° 76,3°			75,6° 76,0° 76,3°			75,7° 76,0° 76,3°
Longueur du tube supérieur (mm)	574 573 572			605 604 603			627 626 626			660 659 658
Longueur du tube de direction (mm)	100			105			115			125
Angle du tube de direction	63,1° 63,5° 63,9°			63,2° 63,5° 63,9°			63,2° 63,6° 63,9°			63,3° 63,6° 63,9°
Déport de fourche (mm)	44			44			44			44
Chasse (mm)	143,9 141,1 138,1			143,6 140,8 138			143,3 140,6 137,8			143 140 137
Empattement (mm)	1194 1193 1193			1226 1225 1225			1250 1250 1249			1285 1285 1285
Longueur des bases (mm)	440 439 438			440 439 438			440 439 438			440 439 438
Hauteur du boîtier de pédalier (mm)	30 25 21			31 26 21			30 26 21			31 26 21
Stack (mm)	626 623 621			631 628 625			640 638 635			650 647 644
Reach (mm)	413 417 421			443 447 451			463 467 471			494 497 501
Hauteur d'enjambement (mm)	725 729 734			739 743 748			762 760 765			773 778 783
Longueur de potence (mm)	40			40			50			50
Longueur des manivelles (mm)	165			170			170			170
Diamètre des roues	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F]

GIANT Suisse se réserve le droit de modifier les spécifications sans préavis. Photos non contractuelles.