

TRINITY ADVANCED PRO TRI FRAMESET



SPECS

RAMME	
STØRRELSE	XS, S, M, L
FARGE	Rainbow Black
RAMME	Advanced-Grade Composite
GAFFEL	Advanced-Grade Composite, alloy OverDrive steerer
DEMPER	N/A
KOMPONENTER	
STYRE	Giant Trinity Composite base bar with ski bend
SETEPINNE	Giant Trinity Composite

GEOMETRI

RAMME	XS	S	M
Seat Tube Length (mm)	460	490	515
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	509	528	541
Head Tube Length (mm)	80	110	140
Head Tube Angle	73,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	61	61	61
Wheelbase (mm)	967	988	1003
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	65	65	65
Stack (mm)	482	510	539
Reach (mm)	398	410	417
Stand Over Height (mm)	742	767	790
Handlebar Width (mm)	400	400	400
Stem Length (mm)	80	80	80
Crank Length (mm)	165	170	172,5
Wheel Size	700C	700C	700C
Arm Pad Stack	582-642 (Tri) 550-600 (TT)	612-672 (Tri) 580-630 (TT)	640-700 (Tri) 610-660 (TT)
Arm Pad Reach	394-454 (Tri) 403-463 (TT)	406-466 (Tri) 415-475 (TT)	413-473 (Tri) 422-482 (TT)

Alle spesifikasjonene kan endres uten varsel.