

# TRINITY ADVANCED PRO TRI FRAMESET **GIANT**



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Rainbow Black
OKVIR	Advanced-Grade Composite
VILICE	Advanced-Grade Composite, alloy OverDrive steerer
AMORTIZER	N/A
KOMPONENTE	
KRMILO	Giant Trinity Composite base bar with ski bend
OPORA SEDEŽA	Giant Trinity Composite

## GEOMETRIJA

OKVIR	XS	S	M
Dolžina sedežne cevi (mm)	460	490	515
Kot sedežne cevi	77,0°	77,0°	77,0°
Top Tube Length (mm)	509	528	541
Višina glave okvirja (mm)	80	110	140
Krmlni kot	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	40	40	40
Trail (mm)	61	61	61
Medosna razdalja (mm)	967	988	1003
Dolžina cevi ob verigi (mm)	405	405	405
Bottom Bracket Drop (mm)	65	65	65
Oddaljenost zgornje cevi od gonilne osi (mm)	482	510	539
Doseg (mm)	398	410	417
Višina zgornje cevi (mm)	742	767	790
Širina krmila (mm)	400	400	400
Dolžina opore krmila (mm)	80	80	80
Dolžina gonilke (mm)	165	170	172,5
Velikost obročnikov	700C	700C	700C
Arm Pad Stack	582-642 (Tri)   550-600 (TT)	612-672 (Tri)   580-630 (TT)	640-700 (Tri)   610-670 (TT)
Arm Pad Reach	394-454 (Tri)   403-463 (TT)	406-466 (Tri)   415-475 (TT)	413-473 (Tri)   422-482 (TT)

Vse navedene specifikacije se lahko spremenijo brez obvestila.