TRINITY ADVANCED SL 0

SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Prism Pearl
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORGAFFEL	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	AeroDrive base bar with Sync rest armset, 10 and 15-degree extension wedge
FREMPIND	AeroDrive integrated stem
SADELPIND	Trinity composite
SADEL	Giant Contact SL Tri
GEARGRUPPE	
SKIFTEGREB	SRAM AXS Wire Blips - extension and basebar mounted
BAGSKIFTER	SRAM RED AXS E1
BREMSER	SRAM RED Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BREMSEGREB	SRAM RED Aero
KASSETTE	SRAM RED E1, 12-speed, 10x33
KÆDE	SRAM RED E1
KRANKSÆT	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
KRANKBOKS	SRAM DUB, ceramic, press fit

HJUL	
FÆLGE	CADEX 4-Spoke Disc WheelSystem
NAV	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40, 40T ratchet driver, CenterLock, 12mm thru-axle
EGER	CADEX 4-Spoke Disc WheelSystem
DÆK	CADEX Aero, tubeless, 700x28c, folding
EKSTRA	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
GRÆNSER	
MAX DÆKSTØRRELSE	30mm

Pris: 95.289,00 kr.

GEOMETRI

RAMME	S	M	L
Sadelrørslængde (mm)	508	539	565
Sadelrørsvinkel	77,0°	77,0°	77,0°
Overrørslængde (mm)	530	554	579
Kronrørslængde (mm)	105	125	145
Kronrøsvinkel	73,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	40	40	40
Sti (mm)	63	63	63
Akselafstand (mm)	988	1013	1039
Kædestagslængde (mm)	405	405	405
Krankboks drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Skridthøjde (mm)	786	814	838
Styrbredde (mm)	400	400	400
Pedalarmslængde (mm)	165	170	172,5
Hjulstørrelse	700C	700C	700C
Armstøtte stack	605-685	624-704	643-723
Armstøtte reach	355-430	375-450	395-470

Alle de anførte specifikationer kan ændres uden varsel.