

# TRINITY ADVANCED SL 0



## SPECS

| FRAME           |                                                                               |
|-----------------|-------------------------------------------------------------------------------|
| SIZES           | S, M, L                                                                       |
| COLOURS         | Gloss Carbon/Prismatic Haze                                                   |
| FRAME           | Advanced SL-Grade Composite, 12x142mm thru-axle, disc                         |
| FORK            | Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc |
| COMPONENTS      |                                                                               |
| HANDLEBAR       | AeroDrive base bar with Sync armrest set, 10 and 15 degree extension wedges   |
| GRIPS           | Trinity                                                                       |
| STEM            | AeroDrive integrated stem                                                     |
| SEATPOST        | Trinity Composite                                                             |
| SADDLE          | Giant Contact SL Tri                                                          |
| PEDALS          | Not included                                                                  |
| ARM REST KIT    | Sync rest armset                                                              |
| EXTENSION BARS  | 10 and 15-degree extension wedge                                              |
| DRIVETRAIN      |                                                                               |
| SHIFTERS        | SRAM eTap AXS WireBlips - extension and basebar mounted                       |
| REAR DERAILLEUR | SRAM RED AXS E1                                                               |
| BRAKES          | SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm          |
| BRAKE LEVERS    | SRAM S-900 Aero                                                               |
| CASSETTE        | SRAM RED E1, 12-speed, 10x33                                                  |
| CHAIN           | SRAM RED E1                                                                   |
| CRANKSET        | SRAM RED 1 E1 AXS, 48t with SRAM power meter                                  |
| BOTTOM BRACKET  | SRAM DUB, ceramic, press fit                                                  |

| WHEELS             |                                                                                                                                   |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| RIMS               | CADEX 4-Spoke Disc WheelSystem                                                                                                    |
| HUBS               | [F] CADEX Low Friction Hub, CenterLock, 12mm thru-axle [R] CADEX Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle |
| SPOKES             | CADEX 4-Spoke Disc WheelSystem                                                                                                    |
| TYRES              | CADEX Aero, tubeless, 700x25c (26.5mm), folding                                                                                   |
| EXTRAS             | Bento box top tube storage, hydration kit, computer mount, factory tubeless set up, 30mm max tyre size                            |
| LIMITS             |                                                                                                                                   |
| MAX TYRE CLEARANCE | 30mm                                                                                                                              |

Price: £10,499.00

## GEOMETRY

| FRAME                    | S                            | M                            | L                            |
|--------------------------|------------------------------|------------------------------|------------------------------|
| Seat Tube Length (mm)    | 508                          | 538                          | 565                          |
| Seat Tube Angle          | 77.0°                        | 77.0°                        | 77.0°                        |
| Top Tube Length (mm)     | 530                          | 554                          | 579                          |
| Head Tube Length (mm)    | 105                          | 125                          | 145                          |
| Head Tube Angle          | 73.0°                        | 73.0°                        | 73.0°                        |
| Fork Rake (mm)           | 40                           | 40                           | 40                           |
| Trail (mm)               | 63                           | 63                           | 63                           |
| Wheelbase (mm)           | 988                          | 1013                         | 1039                         |
| Chain Stay Length (mm)   | 405                          | 405                          | 405                          |
| Bottom Bracket Drop (mm) | 70                           | 70                           | 70                           |
| Stack (mm)               | 513                          | 532                          | 551                          |
| Reach (mm)               | 412                          | 432                          | 452                          |
| Stand Over Height (mm)   | 786                          | 814                          | 838                          |
| Handlebar Width (mm)     | 400                          | 400                          | 400                          |
| Crank Length (mm)        | 165                          | 170                          | 172.5                        |
| Wheel Size               | 700C                         | 700C                         | 700C                         |
| Arm Pad Stack            | (TRI) 653-733   (TT) 605-685 | (TRI) 672-752   (TT) 624-704 | (TRI) 691-771   (TT) 643-725 |
| Arm Pad Reach            | (TRI) 340-415   (TT) 355-430 | (TRI) 360-435   (TT) 375-450 | (TRI) 380-455   (TT) 395-470 |
| Pad Reach Min (mm)       | 338                          | 358                          | 378                          |
| Pad Reach Max (mm)       | 413                          | 433                          | 453                          |

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.