

TRINITY ADVANCED SL 0



SPECS

FRAME	
SIZES	S, M, L
COLOURS	Gloss Carbon/Prismatic Haze
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15 degree extension wedges
GRIPS	Trinity
STEM	AeroDrive integrated stem
SEATPOST	Trinity Composite
SADDLE	Giant Contact SL Tri
ARM REST KIT	Sync rest armset
EXTENSION BARS	10 and 15-degree extension wedge
DRIVETRAIN	
SHIFTERS	SRAM eTap AXS WireBlips - extension and basebar mounted
REAR DERAILLEUR	SRAM RED AXS E1
BRAKES	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero
CASSETTE	SRAM RED E1, 12-speed, 10x33
CHAIN	SRAM RED E1
CRANKSET	SRAM RED 1 E1 AXS, 48t with SRAM power meter
BOTTOM BRACKET	SRAM DUB, ceramic, press fit

WHEELS	
RIMS	CADEX 4-Spoke Disc WheelSystem
HUBS	[F] CADEX Low Friction Hub, CenterLock, 12mm thru-axle [R] CADEX Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX 4-Spoke Disc WheelSystem
TYRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	Bento box top tube storage, hydration kit, computer mount, factory tubeless set up, 30mm max tyre size
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: €12,000.00

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	508	538	565
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	530	554	579
Head Tube Length (mm)	105	125	145
Head Tube Angle	73.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	63	63	63
Wheelbase (mm)	988	1013	1039
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stand Over Height (mm)	786	814	838
Handlebar Width (mm)	400	400	400
Crank Length (mm)	165	170	172.5
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704	(TRI) 691-771 (TT) 643-725
Arm Pad Reach	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450	(TRI) 380-455 (TT) 395-470
Pad Reach Min (mm)	338	358	378
Pad Reach Max (mm)	413	433	453

All specifications listed are subject to change without notice.