

TRINITY ADVANCED SL 0



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Prism Pearl
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync rest armset, 10 and 15-degree extension wedge
STEM	AeroDrive integrated stem
SEATPOST	Trinity composite
SADDLE	Giant Contact SL Tri
DRIVETRAIN	
SHIFTERS	SRAM AXS Wire Blips - extension and basebar mounted
REAR DERAILLEUR	SRAM RED AXS E1
BRAKES	SRAM RED Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM RED Aero
CASSETTE	SRAM RED E1, 12-speed, 10x33
CHAIN	SRAM RED E1
CRANKSET	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, ceramic, press fit

WHEELS	
RIMS	CADEX 4-Spoke Disc WheelSystem
HUBS	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40, 40T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	CADEX 4-Spoke Disc WheelSystem
TIRES	CADEX Aero, tubeless, 700x28c, folding
EXTRAS	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRY

FRAME	XXS	XS	S	M	L
Seat Tube Length (mm)	440	477	508	538	565
Seat Tube Angle	77,0°	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530	554	579
Head Tube Length (mm)	65	85	105	125	145
Head Tube Angle	71,0°	72,0°	73,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40	40	40
Trail (mm)	79	69	63	63	63
Wheelbase (mm)	969	974	988	1013	1039
Chain Stay Length (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	70	70	70
Stack (mm)	467	490	513	532	551
Reach (mm)	387	397	412	432	452
Stand Over Height (mm)	733	758	786	814	838
Handlebar Width (mm)	400	400	400	400	400
Crank Length (mm)	160	160	165	170	172,5
Wheel Size	700C	700C	700C	700C	700C
Arm Pad Stack	556-640	582-662	605-685	624-704	643-723
Arm Pad Reach	326-400	339-414	355-430	375-450	395-470

All specifications listed are subject to change without notice.