

TRINITY ADVANCED SL 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Prism Pearl
RAHMEN	Advanced SL-grade composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTEN	
LENKER	AeroDrive base bar with Sync rest armset, 10 and 15-degree extension wedge
VORBAU	AeroDrive integrated stem
SATTELSTÜTZE	Trinity composite
SATTEL	Giant Contact SL Tri
ANTRIEB	
SCHALTHEBEL	SRAM AXS Wire Blips - extension and basebar mounted
SCHALTWERK	SRAM RED AXS E1
BREMSEN	SRAM RED Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BREMSEBEL	SRAM RED Aero
KASSETTE	SRAM RED E1, 12-speed, 10x33
KETTE	SRAM RED E1
KURBEL	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
TRETLAGER	SRAM DUB, ceramic, press fit

LAUFRÄDER	
FELGEN	CADEX 4-Spoke Disc WheelSystem
NABE	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40, 40T ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	CADEX 4-Spoke Disc WheelSystem
REIFEN	CADEX Aero, tubeless, 700x28c, folding
EXTRAS	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIEDATEN

RAHMEN	XXS	XS	S	M	L
Sitzrohrlänge (mm)	452	477	508	539	565
Sitzrohrwinkel	77.0°	77.0°	77.0°	77.0°	77.0°
Oberrohrlänge (mm)	494	510	530	554	579
Steuerrohr-Länge (mm)	65	85	105	125	145
Steuerrohr-Winkel	71.0°	72.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	40	40	40	40	40
Trail (mm)	79	69	63	63	63
Radstand (mm)	969	974	988	1013	1039
Kettenstreben-Länge (mm)	405	405	405	405	405
Tretlager-Höhe (mm)	70	70	70	70	70
Stack (mm)	467	490	513	532	551
Reach (mm)	387	397	412	432	452
Überstandshöhe (mm)	733	758	786	814	838
Lenkerbreite (mm)	400	400	400	400	400
Kurbellänge (mm)	160	160	165	170	172.5
Radgrösse	700C	700C	700C	700C	700C
Arm Pad Stack	556-640	582-662	605-685	624-704	643-723
Arm Pad Reach	326-400	339-414	355-430	375-450	395-470

Spezifikations-, Preis- und Farbänderungen vorbehalten.