

TRINITY ADVANCED SL 0



TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Carbon/Prismatic Haze
CADRE	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	AeroDrive Base Bar with integrated stem combo
POTENCE	AeroDrive Base Bar with integrated stem
TIGE DE SELLE	Trinity Composite
SELLE	Giant Contact SL Tri
KIT POUR PROLONGATEURS	Sync rest armset
PROLONGATEURS	10 and 15-degree extension wedge
DÉRAILLEUR	
MANETTES	SRAM eTap AXS WireBlips - extension and basebar mounted - 1x12 s
DÉRAILLEUR ARRIÈRE	SRAM RED AXS E1
FREINS	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
LEVIERS DE FREIN	SRAM S-900 Aero
CASSETTE	SRAM RED E1, 12-speed, 10x33
CHAÎNE	SRAM RED E1
PÉDALIER	SRAM RED 1 E1 AXS, 48t (max 55T) with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	CADEX 4-Spoke Disc WheelSystem / Ceramic Bearing
MOYEUX	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	CADEX 4-Spoke Disc WheelSystem
PNEUS	CADEX Aero, tubeless, 700x25c (26.5mm effective - max 30C), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	30mm

Prix Public Conseillé: 12 000,00 €

GÉOMÉTRIE

CADRE	XS	S	M
Longueur de tube de selle (mm)	477	508	538
Angle de tube de selle	77,0°	77,0°	77,0°
Longueur du tube supérieur (mm)	510	530	554
Longueur du tube de direction (mm)	85	105	125
Angle du tube de direction	72,0°	73,0°	73,0°
Déport de fourche (mm)	40	40	40
Trail (mm)	69	63	63
Empattement (mm)	974	988	1013
Longueur des bases (mm)	405	405	405
Drop du boîtier de pédalier (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Hauteur en statique (mm)	758	786	814
Largeur de cintre (mm)	400	400	400
Longueur des manivelles (mm)	160	165	170
Diamètre des roues	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-
Longueur des prolongateurs minimale (mm)	323	338	358
Longueur des prolongateurs maximale (mm)	398	413	433