

TRINITY ADVANCED SL 0



TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Prism Pearl
CADRE	Advanced SL-grade composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	AeroDrive base bar with Sync rest armset, 10 and 15-degree extension wedge
POTENCE	AeroDrive integrated stem
TIGE DE SELLE	Trinity composite
SELLE	Giant Contact SL Tri
DÉRAILLEUR	
MANETTES	SRAM AXS Wire Blips - extension and basebar mounted
DÉRAILLEUR ARRIÈRE	SRAM RED AXS E1
FREINS	SRAM RED Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
LEVIER DE FREIN	SRAM RED Aero
CASSETTE	SRAM RED E1, 12-speed, 10x33
CHAÎNE	SRAM RED E1
PÉDALIER	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOITIER DE PÉDALIER	SRAM DUB, ceramic, press fit

ROUES	
JANTES	CADEX 4-Spoke Disc WheelSystem
MOYEUX	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40, 40T ratchet driver, CenterLock, 12mm thru-axle
RAYONS	CADEX 4-Spoke Disc WheelSystem
PNEUS	CADEX Aero, tubeless, 700x28c, folding
EXTRAS	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
LIMITES	
DÉGAGEMENT MAX DES PNEUS	30mm

Prix Public Conseillé: 12 000,00 €

GÉOMÉTRIE

CADRE	XS	S	M	L
Longueur de tube de selle (mm)	477	508	538	565
Angle de tube de selle	77,0°	77,0°	77,0°	77,0°
Longueur du tube supérieur (mm)	510	530	554	579
Longueur du tube de direction (mm)	85	105	125	145
Angle du tube de direction	72,0°	73,0°	73,0°	73,0°
Déport de fourche (mm)	40	40	40	40
Trail (mm)	69	63	63	63
Empattement (mm)	974	988	1013	1039
Longueur des bases (mm)	405	405	405	405
Drop du boitier de pédalier (mm)	70	70	70	70
Stack (mm)	490	513	532	551
Reach (mm)	397	412	432	452
Hauteur en statique (mm)	758	786	814	838
Largeur de cintre (mm)	400	400	400	400
Longueur des manivelles (mm)	160	165	170	172,5
Diamètre des roues	700C	700C	700C	700C
Arm Pad Stack	582-662	605-685	624-704	643-723
Arm Pad Reach	339-414	355-430	375-450	395-470

Produits conformes aux exigences de sécurité (décret n° 2016-364 du 29 mars 2016).
GIANT France se réserve le droit de modifier les spécifications sans préavis.