



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Carbon/Prismatic Haze
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VILICA	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTE	
VOLAN	AeroDrive base bar
LULA VOLANA	AeroDrive integrated stem
CIJEV SJEDALA	Trinity Composite
SJEDALO	Giant Contact SL Tri
ARM REST KIT	Sync rest armset
EXTENSION BARS	10 and 15-degree extension wedge
POGON	
RUČICE MJENJAČA	SRAM eTap AXS WireBlips - extension and basebar mounted
STRAŽNJI MJENJAČ	SRAM RED AXS E1
KOČNICE	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
RUČICE KOČNICA	SRAM S-900 Aero
KAZETA	SRAM RED E1, 12-speed, 10x33
LANAC	SRAM RED E1
POGON	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	CADEX 4-Spoke Disc WheelSystem
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	CADEX 4-Spoke Disc WheelSystem
GUME	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODACI	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIJA

OKVIR	XS	S
Dužina cijevi sjedala (mm)	477	508
Kut cijevi sjedala	77,0°	77,0°
Dužina gornje cijevi (mm)	510	530
Dužina prednje cijevi (mm)	85	105
Kut vilice	72,0°	73,0°
Zakrivljenost vilice (offset) (mm)	40	40
Staza (mm)	69	63
Međuosovinski razmak kotača (mm)	974	988
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405
Položaj osovine pogona (mm)	70	70
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	490	513
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	397	412
Prekoračna visina (mm)	758	786
Širina volana (mm)	400	400
Dužina poluge pedale (mm)	160	165
Veličina kotača	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662 (TRI) 653-733	
Arm Pad Reach	(TRI) 323-398 (TT) 339-414 (TRI) 340-415	
Pad Reach Min (mm)	323	338
Pad Reach Max (mm)	398	413

Sve navedene specifikacije podložne su promjeni bez prethodne najave.