

# TRINITY ADVANCED SL 0

**GIANT**



## SPECIFICATIES

FRAME	
MATEN	XS, S, M, L
KLEUREN	Carbon/Prismatic Haze
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	AeroDrive base bar
STUURPEN	AeroDrive integrated stem
ZADELPEN	Trinity Composite
ZADEL	Giant Contact SL Tri
ARM REST KIT	Sync rest armset
EXTENSION BARS	10 and 15-degree extension wedge
AFMONTAGE	
SHIFTERS	SRAM eTap AXS WireBlips - extension and basebar mounted
ACHTERDERAILLEUR	SRAM RED AXS E1
REMMEN	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
REMHENDELS	SRAM S-900 Aero
CASSETTE	SRAM RED E1, 12-speed, 10x33
AANDRIJVING	SRAM RED E1
CRANKSET	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	CADEX 4-Spoke 1K Disc WheelSystem
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	CADEX 4-Spoke 1K Disc WheelSystem
BANDEN	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRA'S	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Adviesprijs: € 11.999,00

## GEOMETRIE

FRAME	S	M	L
Zitbuis lengte (mm)	508	538	565
Zitbuis hoek	77,0°	77,0°	77,0°
Frame Lengte (horizontaal) (mm)	530	554	579
Balhoofdbuis Lengte (mm)	105	125	145
Balhoofdbuis Hoek	73,0°	73,0°	73,0°
Vork Sprong (mm)	40	40	40
Naloop (mm)	63	63	63
Wielbasis (mm)	988	1013	1039
Liggende achtervork lengte (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stand Over Height (mm)	786	814	838
Stuur breedte (mm)	400	400	400
Cranklengte (mm)	165	170	172,5
Wielmaat	700C	700C	700C
Arm Pad Stack	(TRI) 653-733   (TT) 605-685 (TRI) 672-752   (TT) 624-704 (TRI) 691-771   (TT) 6		
Arm Pad Reach	(TRI) 340-415   (TT) 355-430 (TRI) 360-435   (TT) 375-450 (TRI) 380-455   (TT) 3		
Pad Reach Min (mm)	338	358	378
Pad Reach Max (mm)	413	433	453

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging