

TRINITY ADVANCED SL 0



產品規格

車架	
尺寸	XS, S, M,
顏色	Carbon/Prismatic Haze
車架	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
前叉	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	AeroDrive base bar
把手帶/套	Stratus Lite 2.0
豎桿	AeroDrive integrated stem
座桿	Trinity Composite
坐墊	Giant Contact SL Tri
ARM REST KIT	Sync rest armset
EXTENSION BARS	10 and 15-degree extension wedge
DRIVETRAIN	
變速把手	SRAM eTap AXS WireBlips - extension and basebar mounted
後變速器	SRAM RED AXS E1
煞車系統	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
煞車把手	SRAM S-900 Aero
飛輪	SRAM RED E1, 12-speed, 10x33
鍊條	SRAM RED E1
大齒盤	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET (B B)	SRAM DUB, press fit

輪組	
輪圈	CADEX 4-Spoke Disc WheelSystem
花鼓	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 40t ratchet driver, CenterLock, 12mm thru-axle
輻條	CADEX 4-Spoke Disc WheelSystem
外胎	CADEX Aero, tubeless, 700x25c (26.5mm), folding
其他	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: NT\$368,000

車架幾何

車架	XS	S	M	L
座(立)管長 (mm)	477	508	538	565
座(立)管角度	77.0°	77.0°	77.0°	77.0
上管長度 (mm)	510	530	554	579
頭管長度 (mm)	85	105	125	145
頭管角度	72.0°	73.0°	73.0°	73.0
前叉 (mm)	40	40	40	40
Trail (mm)	69	63	63	63
前後輪距 (mm)	974	988	1013	1035
後下叉長度 (mm)	405	405	405	405
五通下降高度 (mm)	70	70	70	70
頭碗至五通高度 (mm)	490	513	532	551
頭碗至五通長度 (mm)	397	412	432	452
上管至地面高度 (mm)	758	786	814	838
把手寬 (mm)	400	400	400	400
曲柄長度 (mm)	160	165	170	172
輪組尺寸	700C	700C	700C	700C
肘靠上移範圍	(TRI) 629-709 (TT) 582-662 (TRI) 653-733 (TT) 605-685 (TRI) 672-752 (TT) 624-704 (TRI)			
肘靠前伸範圍	(TRI) 323-398 (TT) 339-414 (TRI) 340-415 (TT) 355-430 (TRI) 360-435 (TT) 375-450 (TRI)			
Pad Reach Min (mm)	323	338	358	378
Pad Reach Max (mm)	398	413	433	453

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。