

TRINITY ADVANCED SL 0

GIANT



產品規格

車架	
尺寸	XS, S, M,
顏色	Prism Pearl珍珠白
車架	Advanced SL-grade composite, 12x142mm thru-axle, disc
前叉	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
車把手	AeroDrive base bar with Sync rest armset, 10 and 15-degree extension wedge
豎桿	AeroDrive integrated stem
座桿	Trinity composite
坐墊	Giant Contact SL Tri
DRIVETRAIN	
變速把手	SRAM AXS Wire Blips - extension and basebar mounted
後變速器	SRAM RED AXS E1
煞車系統	SRAM RED Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
煞車把手	SRAM RED Aero
飛輪	SRAM RED E1, 12-speed, 10x33
鏈條	SRAM RED E1
大齒盤	SRAM RED 1 E1 AXS, 48t with SRAM power meter XS:160mm, S:165mm, M:170mm,
BOTTOM BRACKET (B B)	SRAM DUB, ceramic, press fit

輪組	
輪圈	CADEX 4-Spoke Disc WheelSystem
花鼓	[F] CADEX R3 Hub, CenterLock, 12mm thru-axle [R] CADEX R3-C40, 40T ratchet driver, CenterLock, 12mm thru-axle
輻條	CADEX 4-Spoke Disc WheelSystem
外胎	CADEX Aero, tubeless, 700x28c, folding
其他	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: NT\$368,000

車架幾何

車架	XS	S	M	L
座(立)管長 (mm)	477	508	538	565
座(立)管角度	77.0°	77.0°	77.0°	77.0°
上管長度 (mm)	510	530	554	579
頭管長度 (mm)	85	105	125	145
頭管角度	72.0°	73.0°	73.0°	73.0°
前叉 (mm)	40	40	40	40
Trail (mm)	69	63	63	63
前後輪距 (mm)	974	988	1013	1039
後下叉長度 (mm)	405	405	405	405
五通下降高度 (mm)	70	70	70	70
頭碗至五通高度 (mm)	490	513	532	551
頭碗至五通長度 (mm)	397	412	432	452
上管至地面高度 (mm)	758	786	814	838
把手寬 (mm)	400	400	400	400
曲柄長度 (mm)	160	165	170	172.5
輪組尺寸	700C	700C	700C	700C
肘靠上移範圍	582-662	605-685	624-704	643-723
肘靠前伸範圍	339-414	355-430	375-450	395-470

* 捷安特公司對本網站所刊載之產品資料保留修改權利，恕不另行通知(包括有關設備、規格、型號、重量、顏色和材料等)，請以實際產品為主。