



СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Carbon/Matte Carbon
РАМКА	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
ВИЛКА	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
КОМПОНЕНТИ	
КОРМИЛО	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
ЛАПА	AeroDrive integrated stem
КОЛЧЕ ЗА СЕДАЛКА	Trinity Composite
СЕДАЛКА	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
КОМАНДИ	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
ПРЕДЕН ДЕРАЙЛЪОР	SRAM Force AXS
ЗАДЕН ДЕРАЙЛЪОР	SRAM Force AXS D2
СПИРАЧКИ	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	SRAM S-900 Aero AXS
КАСЕТА	SRAM Force, 12-speed, 10x33
ВЕРИГА	SRAM Force D1
КУРБЕЛ	SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm
ГЛАВИНИ	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
СПИЦИ	Giant Aero Carbon Spoke
ГУМИ	CADEX Aero, tubeless, 700x25c (26.5mm), folding
ЕКСТРИ	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	30mm

ГЕОМЕТРИЯ

РАМКА	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Обсер (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Ширина на Кормило (mm)	400	400	400
Дължина на Курбел (mm)	160	165	170
Размер на Каплите	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-700
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

All specifications listed are subject to change without notice.