

TRINITY ADVANCED SL 1



SPECIFIKATIONER

RAMME	
STØRRELSER	XS, S, M, L
FARVER	Ember Violet/Black
RAMME	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FORGAFFEL	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYR	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
GREB / STYRBÅND	Stratus Lite 2.0
FREMPIND	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SADELPIND	Trinity composite
SADEL	Giant Contact SL Tri
GEARGRUPPE	
SKIFTEGREB	SRAM Clics - extension mounted, SRAM Blips - basebar mounted
FORSKIFTER	SRAM Force AXS
BAGSKIFTER	SRAM Force AXS E1
BREMSE	SRAM Force Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BREMSEGREB	SRAM Force Aero AXS
KASSETTE	SRAM Force E1, 12-speed, 10x33
KÆDE	SRAM Force E1
KRANKSÆT	SRAM Force E1 AXS, 37/50 with SRAM power meter XS:165mm, S:170mm, M:170mm, L:172.5mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant SLR 1 50 WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
EGER	SAPIM CX-Ray
DÆK	CADEX Aero, tubeless, 700x28c, folding
EKSTRA	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
GRÆNSER	
MAX DÆKSTØRRELSE	30mm

Pris: 71.469,00 kr.

GEOMETRI

RAMME	S	M	L
Sadelrørslængde (mm)	508	538	565
Sadelrørvinkel	77,0°	77,0°	77,0°
Overrørslængde (mm)	530	554	579
Kronrørslængde (mm)	105	125	145
Kronrørvinkel	73,0°	73,0°	73,0°
Forgaffel fremspring (rake) (mm)	40	40	40
Sti (mm)	63	63	63
Akselafstand (mm)	988	1013	1039
Kædestagslængde (mm)	405	405	405
Krankboks drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Skridthøjde (mm)	786	814	838
Styrbredde (mm)	400	400	400
Pedalarmslængde (mm)	165	170	172,5
Hjulstørrelse	700C	700C	700C
Armstøtte stack	605-685	624-704	643-723
Armstøtte reach	355-430	375-450	395-470

Alle de anførte specifikationer kan ændres uden varsel.