

TRINITY ADVANCED SL 1



SPECS

FRAME	
SIZES	S, M, L
COLOURS	Carbon/Matte Carbon
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STEM	AeroDrive integrated stem
SEATPOST	Trinity Composite
SADDLE	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
SHIFTERS	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
FRONT DERAILLEUR	SRAM Force AXS
REAR DERAILLEUR	SRAM Force AXS D2
BRAKES	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero AXS
CASSETTE	SRAM Force, 12-speed, 10x33
CHAIN	SRAM Force D1
CRANKSET	SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TYRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TYRE CLEARANCE	30mm

Price: £8,250.00

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	508	538	565
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	530	554	579
Head Tube Length (mm)	105	125	145
Head Tube Angle	73.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	63	63	63
Wheelbase (mm)	988	1013	1039
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stand Over Height (mm)	786	814	838
Handlebar Width (mm)	400	400	400
Crank Length (mm)	165	170	172.5
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704	(TRI) 691-771 (TT) 643-725
Arm Pad Reach	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450	(TRI) 380-455 (TT) 395-470
Pad Reach Min (mm)	338	358	378
Pad Reach Max (mm)	413	433	453

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours