

TRINITY ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLOURS	Ember Violet/Black
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
FORK	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
GRIPS	Stratus Lite 2.0
STEM	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SEATPOST	Trinity composite
SADDLE	Giant Contact SL Tri
DRIVETRAIN	
SHIFTERS	SRAM Clics - extension mounted, SRAM Blips - basebar mounted
FRONT DERAILLEUR	SRAM Force AXS
REAR DERAILLEUR	SRAM Force AXS E1
BRAKES	SRAM Force Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM Force Aero AXS
CASSETTE	SRAM Force E1, 12-speed, 10x33
CHAIN	SRAM Force E1
CRANKSET	SRAM Force E1 AXS, 37/50 with SRAM power meter XS:165mm, S:170mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 50 WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
SPOKES	SAPIM CX-Ray
TYRES	CADEX Aero, tubeless, 700x28c, folding
EXTRAS	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: €9,499.00

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	477	508	538	565
Seat Tube Angle	77.0°	77.0°	77.0°	77.0°
Top Tube Length (mm)	510	530	554	579
Head Tube Length (mm)	85	105	125	145
Head Tube Angle	72.0°	73.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40	40
Trail (mm)	69	63	63	63
Wheelbase (mm)	974	988	1013	1039
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	490	513	532	551
Reach (mm)	397	412	432	452
Stand Over Height (mm)	758	786	814	838
Handlebar Width (mm)	400	400	400	400
Crank Length (mm)	160	165	170	172.5
Wheel Size	700C	700C	700C	700C
Arm Pad Stack	582-662	605-685	624-704	643-723
Arm Pad Reach	339-414	355-430	375-450	395-470

All specifications listed are subject to change without notice.