

TRINITY ADVANCED SL 1



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon/Matte Carbon
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STEM	AeroDrive integrated stem
SEATPOST	Trinity Composite
SADDLE	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
SHIFTERS	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
FRONT DERAILLEUR	SRAM Force AXS
REAR DERAILLEUR	SRAM Force AXS D2
BRAKES	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero AXS
CASSETTE	SRAM Force, 12-speed, 10x33
CHAIN	SRAM Force D1
CRANKSET	SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TIRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Price: ₹ 9,499.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Handlebar Width (mm)	400	400	400
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433