

# TRINITY ADVANCED SL 1\*



## SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon/Matte Carbon
FRAME	Advanced SL-grade composite, 12x142mm thru-axle, disc
FORK	Advanced SL-grade composite, full-composite steerer, 12x100mm, disc
SHOCK	N/A
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
GRIPS	Rubber integrated
STEM	AeroDrive integrated stem
SEATPOST	Trinity Composite
SADDLE	Giant Contact SL Tri
PEDALS	N/A
ARM REST KIT	Sync armrest set
DRIVETRAIN	
SHIFTERS	SRAM eTap AXS Wireless Blips - extension and basebar mounted
FRONT DERAILLEUR	SRAM Force AXS, FD-Force-E-E1
REAR DERAILLEUR	SRAM Force AXS, FD-Force-E-E1
BRAKES	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero
CASSETTE	SRAM Force E1 XG-1270, 12-speed, 10-33
CHAIN	SRAM Force-E1, 12-speed
CRANKSET	SRAM Force E1, DUB, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, Press Fit

WHEELS	
RIMS	Giant SLR 1 50 Carbon Disc WheelSystem, [F]50mm, [R]50mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Sapim CX-Ray
TIRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	Bento box top tube storage, hydration kit, computer mount, tubeless prepared, 30mm max tyre size
LIMITS	
MAX TYRE CLEARANCE	30mm

Price: \$12,499.00

## GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709   (TT) 582-662	(TRI) 653-733   (TT) 605-685	(TRI) 672-752   (TT) 624-704
Arm Pad Reach	(TRI) 323-398   (TT) 339-414	(TRI) 340-415   (TT) 355-430	(TRI) 360-435   (TT) 375-451
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. \*Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.