

TRINITY ADVANCED SL 1



TEKNISET TIEDOT

RUNKO	
KOOT	XS, S, M, L
VÄRIT	Ember Violet/Black
RUNKO	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
HAARUKKA	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
KOMONENTIT	
OHJAUSTANKO	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
GRIPIT	Stratus Lite 2.0
OHJAINKANNATIN	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SATULATOLPPA	Trinity composite
SATULA	Giant Contact SL Tri
VOIMANSIIRTO	
VAIHDEVIPU	SRAM Clics - extension mounted, SRAM Blips - basebar mounted
ETUVAIHTAJA	SRAM Force AXS
TAKAVAIHTAJA	SRAM Force AXS E1
JARRUT	SRAM Force Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
JARRUKAHVAT	SRAM Force Aero AXS
RATASPAKKA	SRAM Force E1, 12-speed, 10x33
KETJUT	SRAM Force E1
KAMPISARJA	SRAM Force E1 AXS, 37/50 with SRAM power meter XS:165mm, S:170mm, M:170mm, L:172.5mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant SLR 1 50 WheelSystem, [F]50mm, [R]50mm
NAVAT	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
PINNAT	SAPIM CX-Ray
RENKAAT	CADEX Aero, tubeless, 700x28c, folding
LISÄTIEDOT	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
RAJOITTEET	
MAX RENGASVARA	30mm

Suositushinta: 9 569,00 €

GEOMETRIA

RUNKO	S	M	L
Satulaputken pituus (mm)	508	538	565
Satulaputken kulma	77,0°	77,0°	77,0°
Vaakaputken pituus (mm)	530	554	579
Emäputken pituus (mm)	105	125	145
Emäputken kulma	73,0°	73,0°	73,0°
Haarukan offset (mm)	40	40	40
Trail-mitta (mm)	63	63	63
Akseliväli (mm)	988	1013	1039
Takahaarukan alaputken pituus (mm)	405	405	405
Keskiön pudotus (mm)	70	70	70
Stack-mitta (mm)	513	532	551
Reach-mitta (mm)	412	432	452
Standover-mitta (mm)	786	814	838
Ohjaustangon leveys (mm)	400	400	400
Kammen pituus (mm)	165	170	172,5
Rengaskoko	700C	700C	700C
Käsivarsitynnyypino	605-685	624-704	643-723
Käsivarsitynnyyn ulottuvuus	355-430	375-450	395-470

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.