



SPECIFIKACIJE

| OKVIR               |                                                                                   |
|---------------------|-----------------------------------------------------------------------------------|
| VELIČINE            | XS, S, M, L                                                                       |
| BOJE                | Carbon/Matte Carbon                                                               |
| OKVIR               | Advanced SL-Grade Composite, 12x142mm thru-axle, disc                             |
| VILICA              | Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc     |
| KOMPONENTE          |                                                                                   |
| VOLAN               | AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge        |
| LULA VOLANA         | AeroDrive integrated stem                                                         |
| CIJEV SJEDALA       | Trinity Composite                                                                 |
| SJEDALO             | Giant Contact SL Tri                                                              |
| ARM REST KIT        | Sync armrest set                                                                  |
| POGON               |                                                                                   |
| RUČICE MJENJAČA     | SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted            |
| PREDNJI MJENJAČ     | SRAM Force AXS                                                                    |
| STRAŽNJI MJENJAČ    | SRAM Force AXS D2                                                                 |
| KOČNICE             | SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm              |
| RUČICE KOČNICA      | SRAM S-900 Aero AXS                                                               |
| KAZETA              | SRAM Force, 12-speed, 10x33                                                       |
| LANAC               | SRAM Force D1                                                                     |
| POGON               | SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm |
| OSOVINA POGONA (BB) | SRAM DUB, press fit                                                               |

| KOTAČI             |                                                                                                                                   |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| OBRUČI             | Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm                                                                                      |
| NABE               | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle |
| ŽBICE              | Giant Aero Carbon Spoke                                                                                                           |
| GUME               | CADEX Aero, tubeless, 700x25c (26.5mm), folding                                                                                   |
| DODACI             | TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size                                                  |
| LIMITS             |                                                                                                                                   |
| MAX TIRE CLEARANCE | 30mm                                                                                                                              |

GEOMETRIJA

| OKVIR                                                              | XS                                         | S     |
|--------------------------------------------------------------------|--------------------------------------------|-------|
| Dužina cijevi sjedala (mm)                                         | 477                                        | 508   |
| Kut cijevi sjedala                                                 | 77,0°                                      | 77,0° |
| Dužina gornje cijevi (mm)                                          | 510                                        | 530   |
| Dužina prednje cijevi (mm)                                         | 85                                         | 105   |
| Kut vilice                                                         | 72,0°                                      | 73,0° |
| Zakrivljenost vilice (offset) (mm)                                 | 40                                         | 40    |
| Staza (mm)                                                         | 69                                         | 63    |
| Međuosovinski razmak kotača (mm)                                   | 974                                        | 988   |
| Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)       | 405                                        | 405   |
| Položaj osovine pogona (mm)                                        | 70                                         | 70    |
| Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)   | 490                                        | 513   |
| Horizontalna dužina od osovine pogona do glave okvira (reach) (mm) | 397                                        | 412   |
| Prekoračna visina (mm)                                             | 758                                        | 786   |
| Širina volana (mm)                                                 | 400                                        | 400   |
| Dužina poluge pedale (mm)                                          | 160                                        | 165   |
| Veličina kotača                                                    | 700C                                       | 700C  |
| Arm Pad Stack                                                      | (TRI) 629-709   (TT) 582-662 (TRI) 653-733 |       |
| Arm Pad Reach                                                      | (TRI) 323-398   (TT) 339-414 (TRI) 340-415 |       |
| Pad Reach Min (mm)                                                 | 323                                        | 338   |
| Pad Reach Max (mm)                                                 | 398                                        | 413   |

Sve navedene specifikacije podložne su promjeni bez prethodne najave.