

TRINITY ADVANCED SL 1



SPECIFICATIES

FRAME	
MATEN	S, M, L
KLEUREN	Carbon/Matte Carbon
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VOORVORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
ONDERDELEN	
STUUR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STUURPEN	AeroDrive integrated stem
ZADEL PEN	Trinity Composite
ZADEL	Giant Contact SL Tri
ARMSTEUNSET	Sync armrest set
AFMONTAGE	
SHIFTERS	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
VOORDERAILLEUR	SRAM Force AXS
ACHTTERDERAILLEUR	SRAM Force AXS D2
REMMEN	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
REMHENDELS	SRAM S-900 Aero AXS
CASSETTE	SRAM Force, 12-speed, 10x33
AANDRIJVING	SRAM Force D1
CRANKSET	SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm
NAVEN	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPAKEN	Giant Aero Carbon Spoke
BANDEN	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRA'S	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAXIMALE BANDENVRIJHEID	30mm

Adviesprijs: € 9.499,00

GEOMETRIE

FRAME	S	M	L
Zitbuis Lengte (mm)	508	538	565
Zitbuis Hoek	77,0°	77,0°	77,0°
Frame Lengte (horizontaal) (mm)	530	554	579
Balhoofdbuis Lengte (mm)	105	125	145
Balhoofdbuis Hoek	73,0°	73,0°	73,0°
Vork Sprong (mm)	40	40	40
Naloop (mm)	63	63	63
Wielbasis (mm)	988	1013	1039
Liggende achtervork lengte (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stand Over Height (mm)	786	814	838
Stuur breedte (mm)	400	400	400
Cranklengte (mm)	165	170	172,5
Wielmaat	700C	700C	700C
Arm Pad Stack	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704	(TRI) 691-771 (TT) 6
Arm Pad Reach	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450	(TRI) 380-455 (TT) 3
Pad Reach Min (mm)	338	358	378
Pad Reach Max (mm)	413	433	453

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafgaande kennisgeving wijzigen.