

TRINITY ADVANCED SL 1

GIANT

SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Carbon/Matte Carbon
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
OPORA KRMILA	AeroDrive integrated stem
OPORA SEDEŽA	Trinity Composite
SEDEŽ	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
POGON	
PRESTAVNE ROČICE	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
PREDNJI MENJALNIK	SRAM Force AXS
ZADNJI MENJALNIK	SRAM Force AXS D2
ZAVORE	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
ZAVORNE ROČICE	SRAM S-900 Aero AXS
VERIŽNIK	SRAM Force, 12-speed, 10x33
VERIGA	SRAM Force D1
GONILKE Z VERIŽNIKI	SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm
PESTA	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
NAPERE	Giant Aero Carbon Spoke
PLAŠČI	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODATKI	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIJA

OKVIR	XS	S	M
Dolžina sedežne cevi (mm)	477	508	538
Kot sedežne cevi	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Višina glave okvirja (mm)	85	105	125
Krmilni kot	72,0°	73,0°	73,0°
Zamik vpetja osi (mm)	40	40	40
Trail (mm)	69	63	63
Medosna razdalja (mm)	974	988	1013
Dolžina cevi ob verigi (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	490	513	532
Doseg (mm)	397	412	432
Višina zgornje cevi (mm)	758	786	814
Širina krmila (mm)	400	400	400
Dolžina gonilke (mm)	160	165	170
Velikost obročnikov	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662 (TRI) 653-733 (TT) 605-685 (TRI) 672		
Arm Pad Reach	(TRI) 323-398 (TT) 339-414 (TRI) 340-415 (TT) 355-430 (TRI) 360		
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Vse navedene specifikacije se lahko spremenijo brez obvestila.