

# TRINITY ADVANCED SL 1

GIANT



## SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Carbon/Matte Carbon
RAM	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
GAFFEL	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STAM	AeroDrive integrated stem
SADELSTOLPE	Trinity Composite
SADEL	Giant Contact SL Tri
ARMSTÖDSSATS	Sync armrest set
DRIVLINJA	
VÄXLAR	SRAM eTap Clicks - extension mounted, SRAM eTap Blips - basebar mounted
FRAMVÄXEL	SRAM Force AXS
BAKVÄXEL	SRAM Force AXS D2
BROMSAR	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BROMSSPAKAR	SRAM S-900 Aero AXS
KASSETT	SRAM Force, 12-speed, 10x33
KEDJA	SRAM Force D1
VEVPARTI	SRAM Force AXS, 37/50 with SRAM power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant SLR 1 50 WheelSystem, [F]40mm, [R]40mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
EKRAR	Giant Aero Carbon Spoke
DÄCK	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAFUNKTIONER	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
GRÄNSER	
MAX DÄCKAVSTÅND	30mm

Price: 114 990,00 kr

## GEOMETRY

RAM	S	M	L
Längd sadelrör (mm)	508	538	565
Vinkel sadelrör	77,0°	77,0°	77,0°
Topprörets längd (mm)	530	554	579
Styrhuvud Längd (mm)	105	125	145
Vinkel styrhuvud	73,0°	73,0°	73,0°
Gaffelvinkel (mm)	40	40	40
Spår (mm)	63	63	63
Hjulbas (mm)	988	1013	1039
Kedjestagslängd (mm)	405	405	405
Nedre fäste Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stå över höjden (mm)	786	814	838
Styrets bredd (mm)	400	400	400
Vevlängd (mm)	165	170	172,5
Hjulstorlek	700C	700C	700C
Arm Pad Stack	(TRI) 653-733   (TT) 605-685 (TRI) 672-752   (TT) 624-704 (TRI) 691-771   (TT) 643-723		
Arm Pad Räckvidd	(TRI) 340-415   (TT) 355-430 (TRI) 360-435   (TT) 375-450 (TRI) 380-455   (TT) 395-470		
Pad Räckvidd Min (mm)	338	358	378
Pad Räckvidd Max (mm)	413	433	453

All specifications listed are subject to change without notice.