

TRINITY ADVANCED SL 1



SPECS

RAM	
STORLEKAR	XS, S, M, L
FÄRGER	Ember Violet/Black
RAM	Advanced SL-grade composite, 12x142mm thru-axle, integrated seatpost, disc
GAFFEL	Advanced SL-grade composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTER	
STYRE	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
GREPPAR	Stratus Lite 2.0
STAM	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SADELSTOLPE	Trinity composite
SADEL	Giant Contact SL Tri
DRIVLINJA	
VÄXLAR	SRAM Clics - extension mounted, SRAM Blips - basebar mounted
FRAMVÄXEL	SRAM Force AXS
BAKVÄXEL	SRAM Force AXS E1
BROMSAR	SRAM Force Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BROMSSPAKAR	SRAM Force Aero AXS
KASSETT	SRAM Force E1, 12-speed, 10x33
KEDJA	SRAM Force E1
VEVPARTI	SRAM Force E1 AXS, 37/50 with SRAM power meter XS:165mm, S:170mm, M:170mm, L:172.5mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant SLR 1 50 WheelSystem, [F]50mm, [R]50mm
NAV	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30T ratchet driver, CenterLock, 12mm thru-axle
EKRAR	SAPIM CX-Ray
DÄCK	CADEX Aero, tubeless, 700x28c, folding
EXTRAFUNKTIONER	Bento box top tube storage, hydration kit, computer mount, tubeless prepared
GRÄNSER	
MAX DÄCKAVSTÅND	30mm

Price: 106 000,00 kr

GEOMETRY

RAM	S	M	L
Längd sadelrör (mm)	508	538	565
Vinkel sadelrör	77,0°	77,0°	77,0°
Topprörets längd (mm)	530	554	579
Styrhuvud Längd (mm)	105	125	145
Vinkel styrhuvud	73,0°	73,0°	73,0°
Gaffelvinkel (mm)	40	40	40
Spår (mm)	63	63	63
Hjulbas (mm)	988	1013	1039
Kedjestagslängd (mm)	405	405	405
Nedre fäste Drop (mm)	70	70	70
Stack (mm)	513	532	551
Reach (mm)	412	432	452
Stå över höjden (mm)	786	814	838
Styrets bredd (mm)	400	400	400
Vevlängd (mm)	165	170	172,5
Hjulstorlek	700C	700C	700C
Arm Pad Stack	605-685	624-704	643-723
Arm Pad Räckvidd	355-430	375-450	395-470

All specifications listed are subject to change without notice.