

TRINITY ADVANCED SL 2



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Carbon/Blue Dragonfly
FRAME	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FORK	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
HANDLEBAR	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
STEM	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SEATPOST	Trinity Composite
SADDLE	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
DRIVETRAIN	
SHIFTERS	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
FRONT DERAILLEUR	SRAM Rival AXS
REAR DERAILLEUR	SRAM Rival AXS D2
BRAKES	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRAKE LEVERS	SRAM S-900 Aero AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAIN	SRAM Force D1
CRANKSET	SRAM Rival AXS, 35/48 with Giant Power Halo power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant SLR 2 50 WheelSystem, [F]40mm, [R]40mm
HUBS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPOKES	Giant Aero Carbon Spoke
TIRES	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

Recommended Retail Price: \$9,900.00

GEOMETRY

FRAME	XS	S	M
Seat Tube Length (inch)	18.8	20	21.2
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (inch)	20.1	20.9	21.8
Head Tube Length (inch)	3.3	4.1	4.9
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (inch)	1.6	1.6	1.6
Trail (inch)	2.7	2.5	2.5
Wheelbase (inch)	38.3	38.9	39.9
Chain Stay Length (inch)	15.9	15.9	15.9
Bottom Bracket Drop (inch)	2.8	2.8	2.8
Stack (inch)	19.3	20.2	20.9
Reach (inch)	15.6	16.2	17
Stand Over Height (inch)	29.8	30.9	32
Handlebar Width (inch)	15.7	15.7	15.7
Crank Length (inch)	6.3	6.5	6.7
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662 (TRI) 653-733 (TT) 605-685 (TRI) 672-752 (TT) 624-70		
Arm Pad Reach	(TRI) 323-398 (TT) 339-414 (TRI) 340-415 (TT) 355-430 (TRI) 360-435 (TT) 375-45		
Pad Reach Min (inch)	12.7	13.3	14.1
Pad Reach Max (inch)	15.7	16.3	17

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size*