



CARACTÉRISTIQUES TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COULEURS	Carbon/Blue Dragonfly
CADRE	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPOSANTES	
GUIDON	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
POTENCE	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
TIGE DE SELLE	Trinity Composite
SELLE	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
TRANSMISSION (DRIVETRAIN)	
LEVIER DE VITESSE	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
DÉRAILLEUR AVANT	SRAM Rival AXS
DÉRAILLEUR ARRIÈRE	SRAM Rival AXS D2
FREINS	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
LEVIER DE FREIN	SRAM S-900 Aero AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAÎNE	SRAM Force D1
PÉDALIER	SRAM Rival AXS, 35/48 with power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOÎTIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant SLR 2 50 WheelSystem, [F]40mm, [R]40mm
MOYEURS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Giant Aero Carbon Spoke
PNEUS	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITES	
MAX TIRE CLEARANCE	30mm

Prix de détail: 9 999,00 \$

GÉOMÉTRIE

CADRE	XS	S	M
Longueur du tube de selle (mm)	477	508	538
Angle du tube de selle	77,0°	77,0°	77,0°
Longueur du tube supérieur (top tube) (mm)	510	530	554
Longueur du tube de direction (head tube) (mm)	85	105	125
Angle du tube de direction	72,0°	73,0°	73,0°
Déport (rake) de fourche (mm)	40	40	40
Trail (mm)	69	63	63
Empattement (mm)	974	988	1013
Longueur des bases (mm)	405	405	405
Hauteur du boîtier de pédalier (mm)	70	70	70
Portée Verticale (Stack) (mm)	490	513	532
Portée Horizontale (Reach) (mm)	397	412	431
Hauteur du cadre (mm)	758	787	815
Largeur du Guidon (mm)	400	400	400
Longueur des manivelles (mm)	160	165	170
Diamètre des Roues	700C	700C	700C
Stack de l'appuis bras	(TRI) 629-679 (TT) 582-632 (TRI) 653-733 (TT) 605-685 (TRI) 6		
Reach de l'appuis bras	(TRI) 323-398 (TT) 339-414 (TRI) 340-415 (TT) 355-430 (TRI) 3		
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433