

TRINITY ADVANCED SL 2

GIANT



TECHNIQUES

CADRE	
TAILLES	XS, S, M, L
COLORIS	Carbon/Blue Dragonfly
CADRE	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FOURCHE	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPOSANTS	
CINTRE	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
POTENCE	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
TIGE DE SELLE	Trinity Composite
SELLE	Giant Contact SL Tri
KIT POUR PROLONGATEURS	Sync armrest set
DÉRAILLEUR	
MANETTES	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
DÉRAILLEUR AVANT	SRAM Rival AXS
DÉRAILLEUR ARRIÈRE	SRAM Rival AXS
FREINS	SRAM Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
LEVIER DE FREIN	SRAM Rival AXS
CASSETTE	SRAM Rival, 12-speed, 10x36
CHAÎNE	SRAM Rival
PÉDALIER	SRAM Rival AXS, 35/48 with Giant Power Halo power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOITIER DE PÉDALIER	SRAM DUB, press fit

ROUES	
JANTES	Giant SLR 2 50 WheelSystem
MOYEURS	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
RAYONS	Giant Aero Carbon Spoke
PNEUS	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
ACCESSOIRES	
ECLAIRAGE	Kit d'éclairage avant et arrière à piles
LIMITES	
DÉGAGEMENT MAX DES PNEUS	30mm

Prix Public Conseillé: 7 500,00 €

GÉOMÉTRIE

CADRE	XS	S	M
Longueur de tube de selle (mm)	477	508	538
Angle de tube de selle	77,0°	77,0°	77,0°
Longueur du tube supérieur (mm)	510	530	554
Longueur du tube de direction (mm)	85	105	125
Angle du tube de direction	72,0°	73,0°	73,0°
Déport de fourche (mm)	40	40	40
Trail (mm)	69	63	63
Empattement (mm)	974	988	1013
Longueur des bases (mm)	405	405	405
Drop du boîtier de pédalier (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Hauteur en statique (mm)	758	786	814
Largeur de cintre (mm)	400	400	400
Longueur des manivelles (mm)	160	165	170
Diamètre des roues	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-
Longueur des prolongateurs minimale (mm)	323	338	358
Longueur des prolongateurs maximale (mm)	398	413	433