



SPECIFIKACIJE

OKVIR	
VELIČINE	XS, S, M, L
BOJE	Carbon/Blue Dragonfly
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VILICA	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTE	
VOLAN	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
LULA VOLANA	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
CIJEV SJEDALA	Trinity Composite
SJEDALO	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
POGON	
RUČICE MJENJAČA	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
PREDNJI MJENJAČ	SRAM Rival AXS
STRAŽNJI MJENJAČ	SRAM Rival AXS D2
KOČNICE	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
RUČICE KOČNICA	SRAM S-900 Aero AXS
KAZETA	SRAM Rival, 12-speed, 10x36
LANAC	SRAM Force D1
POGON	SRAM Rival AXS, 35/48 with Giant Power Halo power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
OSOVINA POGONA (BB)	SRAM DUB, press fit

KOTAČI	
OBRUČI	Giant SLR 2 50 WheelSystem, [F]40mm, [R]40mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
ŽBICE	Giant Aero Carbon Spoke
GUME	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DODACI	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIJA

OKVIR	XS	S
Dužina cijevi sjedala (mm)	477	508
Kut cijevi sjedala	77,0°	77,0°
Dužina gornje cijevi (mm)	510	530
Dužina prednje cijevi (mm)	85	105
Kut vilice	72,0°	73,0°
Zakrivljenost vilice (offset) (mm)	40	40
Staza (mm)	69	63
Međuosovinski razmak kotača (mm)	974	988
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	405	405
Položaj osovine pogona (mm)	70	70
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	490	513
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	397	412
Prekoračna visina (mm)	758	786
Širina volana (mm)	400	400
Dužina poluge pedale (mm)	160	165
Veličina kotača	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662 (TRI) 653-733	
Arm Pad Reach	(TRI) 323-398 (TT) 339-414 (TRI) 340-415	
Pad Reach Min (mm)	323	338
Pad Reach Max (mm)	398	413

Sve navedene specifikacije podložne su promjeni bez prethodne najave.