

TRINITY ADVANCED SL 2

GIANT



SPECS

CADRU	
MARIMI	XS, S, M, L
CULORI	Carbon/Blue Dragonfly
CADRU	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
FURCA	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTE	
GHIDON	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
PIPA	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
TIJA SA	Trinity Composite
SA	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
SCHIMBATOR FATA	SRAM Rival AXS
SCHIMBATOR SPATE	SRAM Rival AXS D2
FRANE	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
MANETE FRANA	SRAM S-900 Aero AXS
PINIOANE	SRAM Rival, 12-speed, 10x36
LANT	SRAM Force D1
ANGRENAJ	SRAM Rival AXS, 35/48 with Giant Power Halo power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant SLR 2 50 WheelSystem, [F]40mm, [R]40mm
BUTUCI	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPITE	Giant Aero Carbon Spoke
ANVELOPE	CADEX Aero, tubeless, 700x25c (26.5mm), folding
EXTRAS	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

GEOMETRIE

CADRU	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Handlebar Width (mm)	400	400	400
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI) 672-752 (TT) 624-704
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI) 360-435 (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

Toate specificatiile enumerate se pot schimba fara notificare prealabila.