



ŠPECIFIKÁCIE

RÁM	
VELKOSTI	XS, S, M, L
FARBY	Carbon/Blue Dragonfly
RÁM	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VIDLICA	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTY	
RIADIDLÁ	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
PREDSTAVEC	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
SEDLOVKA	Trinity Composite
SEDADLO	Giant Contact SL Tri
ARM REST KIT	Sync armrest set
POHON	
RADENIE	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
PREŠMYKAČ	SRAM Rival AXS
PREHADZOVAČKA	SRAM Rival AXS D2
BRZDY	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
BRZDOVÉ PÁKY	SRAM S-900 Aero AXS
KAZETA	SRAM Rival, 12-speed, 10x36
REŤAZ	SRAM Force D1
KLUKY	SRAM Rival AXS, 35/48 with Giant Power Halo power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
STREDOVÉ ZLOŽENIE	SRAM DUB, press fit

KOLESÁ	
RÁFIKY	Giant SLR 2 50 WheelSystem, [F]40mm, [R]40mm
NÁBOJE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
ŠPICE	Giant Aero Carbon Spoke
PNEUMATIKY	CADEX Aero, tubeless, 700x25c (26.5mm), folding
DOPLNKY	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITY	
MAXIMÁLNA ŠÍRKA PNEUMATÍK	30mm

Cena: 7 999 €

GEOMETRIA

RÁM	XS	S	M
Dĺžka sedlovej trubky (mm)	477	508	538
Uhol sedlovej trubky	77,0°	77,0°	77,0°
Dĺžka hornej rámovej trubky (mm)	510	530	554
Dĺžka hlavovej trubky (mm)	85	105	125
Uhol hlavovej trubky	72,0°	73,0°	73,0°
Offset vidlice (mm)	40	40	40
Trail (mm)	69	63	63
Rázvor (mm)	974	988	1013
Dĺžka zadnej stavby (mm)	405	405	405
Rozdiel zadnej voči stredovej osi - BB DROP (mm)	70	70	70
Stack - výška riadenia (mm)	490	513	532
Reach (mm)	397	412	432
Výška rámu od zeme (mm)	758	786	814
Šírka riaditok (mm)	400	400	400
Dĺžka klúku (mm)	160	165	170
Rozmer kolies	700C	700C	700C
Arm Pad Stack	(TRI) 629-709 (TT) 582-662	(TRI) 653-733 (TT) 605-685	(TRI)
Arm Pad Reach	(TRI) 323-398 (TT) 339-414	(TRI) 340-415 (TT) 355-430	(TRI)
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433