

# TRINITY ADVANCED SL 2

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	XS, S, M, L
<b>COLORS</b>	Carbon/Blue Dragonfly
<b>FRAME</b>	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
<b>FORK</b>	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
COMPONENTS	
<b>HANDLEBAR</b>	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
<b>STEM</b>	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
<b>SEATPOST</b>	Trinity Composite
<b>SADDLE</b>	Giant Contact SL Tri
<b>ARM REST KIT</b>	Sync armrest set
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM eTap Clics - extension mounted, SRAM eTap Blips - basebar mounted
<b>FRONT DERAILLEUR</b>	SRAM Rival AXS
<b>REAR DERAILLEUR</b>	SRAM Rival AXS D2
<b>BRAKES</b>	SRAM S-900 Aero hydraulic, SRAM PaceLine X rotors [F]160mm, [R]140mm
<b>BRAKE LEVERS</b>	SRAM S-900 Aero AXS
<b>CASSETTE</b>	SRAM Rival, 12-speed, 10x36
<b>CHAIN</b>	SRAM Force D1
<b>CRANKSET</b>	SRAM Rival AXS, 35/48 with Giant Power Halo power meter XS:160mm, S:165mm, M:170mm, L:172.5mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant SLR 2 50 WheelSystem, [F]40mm, [R]40mm
<b>HUBS</b>	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
<b>SPOKES</b>	Giant Aero Carbon Spoke
<b>TIRES</b>	CADEX Aero, tubeless, 700x25c (26.5mm), folding
<b>EXTRAS</b>	TT storage, hydration kit, computer mount, tubeless prepared, 30mm max tire size
LIMITS	
<b>MAX TIRE CLEARANCE</b>	30mm

## GEOMETRY

FRAME	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77.0°	77.0°	77.0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72.0°	73.0°	73.0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Reach (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Handlebar Width (mm)	400	400	400
Crank Length (mm)	160	165	170
Wheel Size	700C	700C	700C
Arm Pad Stack	(TRI) 629-709   (TT) 582-662	(TRI) 653-733   (TT) 605-685	(TRI) 672-752   (TT) 624-704
Arm Pad Reach	(TRI) 323-398   (TT) 339-414	(TRI) 340-415   (TT) 355-430	(TRI) 360-435   (TT) 375-450
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

All specifications listed are subject to change without notice.