

# TRINITY ADVANCED SL TIME TRIAL FRAMESET

**GIANT**

## SPECIFIKACIJE

OKVIR	
VELIKOSTI	XS, S, M, L
BARVE	Carbon/Chrome
OKVIR	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
VILICE	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
KOMPONENTE	
KRMILO	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
OPORA KRMILA	AeroDrive integrated stem
OPORA SEDEŽA	Trinity Composite
ARM REST KIT	Sync armrest set

OBROČNIKI	
DODATKI	Computer mount, down tube bottle and cage, 30mm max tire size
LIMITS	
MAX TIRE CLEARANCE	30mm

## GEOMETRIJA

OKVIR	XXS	XS	S	M	L
Dolžina sedežne cevi (mm)	440	477	508	538	565
Kot sedežne cevi	77,0°	77,0°	77,0°	77,0°	77,0°
Top Tube Length (mm)	493	510	530	554	579
Višina glave okvirja (mm)	65	85	105	125	145
Krmilni kot	71,0°	72,0°	73,0°	73,0°	73,0°
Zamik vpetja osi (mm)	40	40	40	40	40
Trail (mm)	79	69	63	63	63
Medosna razdalja (mm)	969	974	988	1013	1039
Dolžina cevi ob verigi (mm)	405	405	405	405	405
Bottom Bracket Drop (mm)	70	70	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	467	490	513	532	551
Doseg (mm)	387	397	412	432	452
Višina zgornje cevi (mm)	733	758	786	814	838
Širina krmila (mm)	400	400	400	400	400
Dolžina gonilke (mm)	160	160	165	170	172,5
Velikost obročnikov	700C	700C	700C	700C	700C
Arm Pad Stack	556-640	582-662	605-685	624-704	643-723
Arm Pad Reach	326-400	339-414	355-430	375-450	395-470

Ve navedene specifikacije se lahko spremenijo brez obvestila.