

# TRINITY ADVANCED SL TRIATHLON FRAMESET

**GIANT**



## СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	XS, S, M, L
ЦВЯТ	Carbon/Chrome
РАМКА	Advanced SL-Grade Composite, 12x142mm thru-axle, disc
ВИЛКА	Advanced SL-Grade Composite, full-composite steerer, 12x100mm thru-axle, disc
КОМПОНЕНТИ	
КОРМИЛО	AeroDrive base bar with Sync armrest set, 10 and 15-degree extension wedge
ЛАПА	Giant base bar with integrated stem combination with Sync rest set, 10 and 15-degree extension wedge
КОЛЧЕ ЗА СЕДАЛКА	Trinity Composite
ARM REST KIT	Sync armrest set

КАПЛИ	
ЭКСТРИ	TT storage, hydration kit, computer mount, 30mm max tire size
ЛИМИТИ	
MAX TIRE CLEARANCE	30mm

## ГЕОМЕТРИЯ

РАМКА	XS	S	M
Seat Tube Length (mm)	477	508	538
Seat Tube Angle	77,0°	77,0°	77,0°
Top Tube Length (mm)	510	530	554
Head Tube Length (mm)	85	105	125
Head Tube Angle	72,0°	73,0°	73,0°
Fork Rake (mm)	40	40	40
Trail (mm)	69	63	63
Wheelbase (mm)	974	988	1013
Chain Stay Length (mm)	405	405	405
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	490	513	532
Обсер (mm)	397	412	432
Stand Over Height (mm)	758	786	814
Ширина на Кормило (mm)	400	400	400
Дължина на Курбел (mm)	160	165	170
Размер на Каплите	700C	700C	700C
Arm Pad Stack	(TRI) 629-709   (TT) 582-662 (TRI) 653-733   (TT) 605-685 (TRI) 672-752   (TT) 624-708		
Arm Pad Reach	(TRI) 323-398   (TT) 339-414 (TRI) 340-415   (TT) 355-430 (TRI) 360-435   (TT) 375-450		
Pad Reach Min (mm)	323	338	358
Pad Reach Max (mm)	398	413	433

All specifications listed are subject to change without notice.